



## HAWA CLIPO 16 HM IS Bypassing Sliding Door System

**Product #** WEBKIT1213524

### DESCRIPTION

#### Optional Integrated Soft Close Mechanism

HAWA CLIPO 16 HM IS is a top running sliding system for two wooden doors weighing up to 35 lb (16 kg) each, for inslide/inlay applications. The running gear is mortised/rebated into the top of the door. There are different top track options for single and double track applications that can be recessed or surface mounted to the cabinet top. An optional soft-close mechanism (sold separately) is available for inside the track. The bottom of the cabinet does not require a lower guide track in the base.

### ADVANTAGES AND BENEFITS

- High-tech, invisible soft closing system integrated into the running track. - Easy door installation, with clip-on system. - More closing convenience: doors close softly and are pulled into the final position. - Central stopper prevents doors from crossing.

### INCLUDED IN THIS WEBKIT

**Sales unit**



#### Door Follower. CLIPO 16

Product # 1893236171

Bag



#### CLIPO 16 HM IS System Hardware Set

Product # 1893223071

Bag








#### Guide Rail Insert for Bottom of the Door. CLIPO 15/16 H

Product # 1511225

Length of 2.5  
linear meter

## REQUIRED PRODUCTS

Requires ONE of the following products

		Sales unit
	<b>Single Running Track CLIPO 16 H</b> Product # 1890533227250 Overall Length: 98 3/8 in*	Length of 2.5 linear meter
	OR	
	<b>Single Running Track CLIPO 16 H</b> Product # 1890533227350 Overall Length: 11 ft 5 in*	Length of 3.5 linear meter
	OR	
	<b>Single Running Track CLIPO 16 H</b> Product # 1890533229350 Overall Length: 11 ft 5 in*	Length of 3.5 linear meter
	OR	
	<b>Single Running Track CLIPO 16 H</b> Product # 1893229250 Overall Length: 98 3/8 in*	Length of 2.5 linear meter
	OR	
	<b>Double Running Track CLIPO 16 H</b> Product # 1893226250	Length of 2.5 linear meter

## TECHNICAL SPECIFICATIONS

Product #	WEBKIT1213524
Door Material	Wood
Door Movement	Straight Sliding
Detailed Door Movement	Bypassing
Load Capacity	Max. 35.3 lb*
Door Position	Inset/Inlay
Door Thickness	3/4 to 31/32 in*
Roller Type	Axle (Bushing)
Roller Position	Upper
Application	Furniture, Cabinet
Brand	Hawa
Number of Doors	2
Overall Length	98 3/8 in*
Door Height	Max. 55 1/8 in*
Manufacturing Material	Aluminum
Soft-Closing	No
Finish	Satin Aluminum
Door Width	Max. 39 3/8 in*

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## APPLICATION

House, dining room, bedroom, private office, sideboards, kitchen cabinets (top and bottom), bathroom furniture.

## IMPORTANT INFORMATION

- Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

## INCLUDED PRODUCT(S)

We strongly recommend that you order the products TUBECART and CAP (two CAPs per TUBECART) to package this product. Please note that if you do not, returns or claims for packaging defects will not be accepted. Feel free to contact us at [info@richelieu.com](mailto:info@richelieu.com) with questions.

## DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

## PRODUCT PHOTOS

