



## HAWA Porta 100 G Wall or Ceiling Mount Sliding Door Installation

**Product #** WEBKIT1213681

### DESCRIPTION

#### Flexible track mounting for wall or ceiling mounting

The HAWA Porta 100 G is a top hung sliding system for frameless glass door panels weighing up to 220 lb (100 kg) each. The glass is held at the top by two clamp shoes without the need to drill glass or use adhesive (dry glazing). The Combi-Track can be mounted to the wall or ceiling. The toolless clip-on aluminum fascia panel is quick and simple to install.

### ADVANTAGES AND BENEFITS

- Minimal installation height - Glass mounts with well-tested clamp technology - No adhesive required - For wall and ceiling mounting - Running gear concealed behind tool-less clip-on fascia - Quiet and smooth high-quality performance

## INCLUDED IN THIS WEBKIT

**Sales unit**



#### End caps f/wall mounting - 890573052074

Product # 890573052074

Bag



#### Hardware Set for Glass- Hawa Porta 100 G/GU/GM

Product # 893074071

Bag



#### Integrated Soft-Close System for Sliding Door


Product # 893102071

Box

## REQUIRED PRODUCTS!

Requires the following products

**Sales unit**



### HAWA PORTA COMBI Track Series

Product # 890573048250

Length of 2.5  
linear meter

AND



### Integrated Soft-Close System for Sliding Door

Product # 893102071

Box

Requires ONE of the following products

**Sales unit**



### Clip panel f/r.track 3.5 m - 890573050350

Product # 890573050350

Length of 3.5  
linear meter

OR



### Clip panel f/r.track 2.5 m - 890573050250

Product # 890573050250

Length of 2.5  
linear meter

## TECHNICAL SPECIFICATIONS

Product #	WEBKIT1213681
Door Material	Glass
Door Movement	Straight Sliding
Detailed Door Movement	Single sliding
Track Mounting	Ceiling Mount, Wall Mount
Load Capacity	220 lb*
Door Position	In Front of Wall
Door Thickness	5/16 to 1/2 in*
Roller Type	Ball Bearing
Roller Position	Upper
Application	Glass Partition, Standard Access Door
Brand	Hawa
Soft-Closing	Yes
Soft-Close Type	One-Way Operation
Number of Doors	1
Door Height	8 ft 10 in*
Door Width	63 in*

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## APPLICATION

- All-glass/frameless doors - Private living areas - Public and office areas - Projects - Personalized interior design

## IMPORTANT INFORMATION

For the EKU-Porta 100G soft closing in both directions, add the following products to your order: 893102071 and 89311407. The center-to-center distance between rollers should be 570 mm. - Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

---

## DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

**PRODUCT PHOTOS**

