

CINETTO PS40.1 Coplanar Sliding System

Product # WEBKIT1213683

Load Capacity 132 lb*

Number of Doors 1

Overall Length 96 1/2 in*

Opening Towards the right

Door Width 35 to 48 1/4 in*

DESCRIPTION

Door widths varying from 890 mm to 1800 mm

Cinetto PS40.1 Coplanar Sliding System for large cabinet doors weighing up to 132 lb (60 kg) each.

Features:

- Flexible system for one, two, or three wood doors
- Recessed mount hardware, adjustable
- Soft-close mechanism included
- No special cabinet fabrication is required
- Two types of track finishes: silver and stainless steel effect anodized aluminum
- Optional B-moved electronic motor system sold separately

Ideal solution for residential and commercial applications for closets, pantries, large storage millwork, and wardrobes/armoires.

ADVANTAGES AND BENEFITS

- Easy to assemble. - Vertical adjustment: 6 mm +/- 4 mm. - Track can be assembled without screws thanks to the new clip-on system. - Standardized stock: A single cabinet in production can be adapted to three different systems (PS40, PS10 and PS11). - The customer can choose last minute to assembly the PS40 or PS10 system because the cabinet is the same.

INCLUDED IN THIS WEBKIT


Sales unit



Door Straightener/Stiffener

Product # 189BR208B0010

Bag



Lower rail. Ps40.1/PS40.2

Product # 1894073382410

Length of 2.45 linear meter



Rolling Hardware Set - PS40.1/PS40.2

Product # 18940AP2F05S

Box



Upper rail PS40/PS40.1/PS40.2

Product # 89407282410

Length of 2.45
linear meter



Fascia for Upper Track. PS40/PS40.1/PS40.2

Product # 8940738C2410

Length of 2.45
linear meter

TECHNICAL SPECIFICATIONS

Product #	WEBKIT1213683
Door Material	Wood
Door Movement	Coplanar
Track Mounting	Recessed - Inside Ceiling
Door Position	Full Overlay, Inset/Inlay
Door Thickness	3/4 in*
Roller Type	Ball Bearing
Roller Position	Upper
Application	Wardrobe, Pantry, Cabinet, Storage
Brand	CINETTO
Door Height	9 ft 10 in*
Door Installation	Top Hung
Adjustable	Yes
Height Clearance	5 5/32 in*
Manufacturing Material	Aluminum
Soft-Closing	Yes
Soft-Close Type	One-Way Operation
Finish	Satin Aluminum
Brand Model	Cinetto PS40

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

Kitchen, bathroom, office furniture, laundry room, garage, hotel, laboratory, hospital, clinic

IMPORTANT INFORMATION

- Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

PRODUCT PHOTOS

