



HAWA CLIPO 36 HM IS Bypassing Sliding System for Two Cabinet Doors

Product # WEBKIT1214587

DESCRIPTION

Optional hidden soft-closing mechanism


HAWA CLIPO 36 HM IS is a top running sliding system for two wooden doors weighing up to 77 lb (36 kg) each, for inslide/inlay applications. The running gear is mortised/rebated into the top of the door. There are different top track options for single and double track applications that can be recessed or surface mounted to cabinet top. An optional soft-close mechanism (sold separately) is available for inside the track. A unique spring-loaded lower guide wheel and guide rail insert system adjusts to the contour of the cabinet floor as the door travels across the cabinet face.

ADVANTAGES AND BENEFITS

- Optional closing mechanism - Invisible hardware

INCLUDED IN THIS WEBKIT

Sales unit



Guide Rail for HAWA CLIPO 26/36

Product # 1893171250

Length



Hardware set for system Clipo 36 HM IS

Product # 1893358071

Bag



End Cap for End of Track. CLIPO 26/36 H

Product # 1893354071

Bag of 2 units



REQUIRED PRODUCTS

Requires ONE of the following products

Sales unit



Single Running Track for Screw Fixing

Product # 1893325250

Overall Length: 98 3/8 in*

Length of 2.5 linear meter



Single Running Track for Screw Fixing

OR

OR

OR)

Product # 1893325350

Overall Length: 11 ft 5 in*

Length of 3.5 linear meter



Double Running Track for Screw Fixing Product # 1893328250

Overall Length: 98 3/8 in*

Length of 2.5 linear meter



Double Running Track for Screw Fixing Product # 1893328350

Overall Length: 11 ft 5 in*

Length of 3.5 linear meter



TECHNICAL SPECIFICATIONS

Product #	WEBKIT1214587
Door Material	Wood
Door Movement	Straight Sliding
Detailed Door Movement	Bypassing
Track Mounting	Wall Mount, Recessed - Inside Ceiling
Load Capacity	79.4 lb*
Door Thickness	3/4 to 31/32 in*
Roller Type	Axle (Bushing)
Roller Position	Lower
Application	Closet and Walk-In Closet, Pantry, Furniture, Cabinet, Storage
Brand	Hawa
Number of Doors	2
Door Height	Max. 94 1/2 in*
Adjustable	Yes
Track type	Single
Soft-Closing	No
Door Width	Max. 39 3/8 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, <u>click here</u>.

IMPORTANT INFORMATION

- Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

APPLICATION

Private living, eating, and sleeping areas, private and public office areas, sideboards, wall cabinets and base units in kitchens, base units in bathrooms



DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

PRODUCT PHOTOS



