



HAWA Variofold 80/H System for End Folding Partition Wall

Product # WEBKIT1216582

Number of Doors 2 + 2

DESCRIPTION

HAWA-Variofold 80/H

HAWA Variofold 80/H system for end folding partition wall for wood doors weighing up to 176 lb (80 kg) each.

- No bottom guide channel for up to two folding panels.
- Lower guide channel used for greater stability for multiple folding door panels.
- Standard configuration is designed for door thickness of 1 3/8 in (35 mm) to 1 3/4 in (45 mm).
- With special door preparation thicker door panels of 1 3/4 in (46 mm) to 2 1/4 in (57 mm) are possible.




For special applications and assistance contact the Sliding Technical Team by email:
In Canada: infomoveablewallca@richelieu.com
In USA: infomoveablewallusa@richelieu.com

For best results provide a sketch and/or images of your desired end result.

ADVANTAGES AND BENEFITS

- Minimum panel width: 500 mm (1'7 11/16") - Maximum panel width: 900 mm (2'11 7/16") - Panel thickness: 35 mm to 45 mm (1 3/8" to 1 25/32") - Maximum panel weight: 80 kg (176 lb) - Left and right-hand, inwards or outwards-opening installations all use the same components - A communicating pivot door can be added to the panel stack, or the opposing end - Equal-width panels for simple planning - Vertical adjustment: ± 3 mm (1/8") - Light and quiet running

INCLUDED IN THIS WEBKIT

		Sales unit
	Hollow Seal, 10 m Roll Product # 891965790	Bag
	Pivot Bearing, Basic Set - Hawa Variofold 80H Product # 65919534D10	Box
	Drilled Top Track - 6 m (19' 8") Product # 891685210	Length of 6 linear meter



3-Axis Adjustable Concealed Hinges
Product # 896002106

Set of 3 units

TECHNICAL SPECIFICATIONS

Product #	WEBKIT1216582
Door Material	Wood
Door Movement	Folding
Detailed Door Movement	End folding, Bifolding
Track Mounting	Ceiling Mount
Load Capacity	176 lb*
Door Thickness	1 3/8 to 1 25/32 in*
Brand	Hawa
Overall Length	19 ft 8 in*
Manufacturing Material	Aluminum
Door Width	19 5/8 to 35 3/8 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

- Room divisions

IMPORTANT INFORMATION

- Supports a maximum weight of 300 kg (660 lb) in the stacking area. - Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

