



Pro Series Robuste Strap Mount Sliding System

Product # WEBKIT1216650

Overall Length 98 3/8 in*

Finish Matte Black

Style Rustic

Number of Doors 1

DESCRIPTION

Flat bar wall mount barn door style

The professional grade Pro Series Robuste System is made for wood doors up to 220 lb (100 kg).

- Steel flat bar track set with direct mount wall fasteners and standoffs
- Strap mount ball bearing wheels with through-bolt fastener
- Built-in anti-derailing device
- Pre-drilled tracks for installation of soft-close mechanism, 176 lb (80 kg) capacity (sold separately)
- Drywall anti-compression discs
- Adjustable wall mount bottom guide



This barn door system is designed for high-use hospitality and commercial applications.

IMPORTANT: The minimum door width is 36 in (914 mm) when using a soft-close mechanism, and the maximum door weight is 176 lb (80 kg).

ADVANTAGES AND BENEFITS

- Safe system for heavy doors - Solid commercial grade hardware - Quick and secure installation - High-use applications - Drywall compression resistance and track stability - Smooth movement

INCLUDED IN THIS WEBKIT

		Sales unit
	Pro Series Robuste Single Flat Track Set Product # 89TSQ04390	Box
	Pro Series Robuste Strap Mount Hardware Set Product # 89TSQ04190	Box



Internal Wall Support Disc 25464100

Product # 89TY90042640090

Thickness: 15/32 in*

Bag



Internal Wall Support Disc 25464100

Product # 89TY90042630090

Thickness: 1/8 in*

Bag



Lower Guide Channel

Product # 89TY901821511

Bag

TECHNICAL SPECIFICATIONS

Product #	WEBKIT1216650
Door Material	Wood
Door Movement	Straight Sliding
Detailed Door Movement	Single sliding
Track Mounting	Wall Mount
Load Capacity	Max. 220 lb*
Door Thickness	1 3/8 to 1 25/32 in*
Roller Type	Ball Bearing, Axle (Bushing)
Roller Position	Upper
Application	Standard Access Door, Barn Door
Brand	Richelieu
Screw/Nail Included	Yes
Soft-Closing	No
Displayed in These Showrooms	Toronto
Door Height	9 ft 10 in*
Door Width	23 7/8 to 50 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

IMPORTANT: The minimum door width is 36 in (914 mm) when using a soft-close mechanism, and the maximum door weight is 176 lb (80 kg). - Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant on this product.

DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

PRODUCT PHOTOS

