



HAWA SYMMETRIC 80/Z Biparting Synchronized System

Product # WEBKIT1216806

Overall Length 13 ft 1 in*

Door Width 19 5/8 to 39 3/8 in*

DESCRIPTION

Simultaneous opening

The HAWA SYMMETRIC 80/Z Biparting Synchronized system is for two wood doors sliding in opposite directions on one track, each weighing up to 176 lb (80 kg).

Features:




- Pulley system attaches to both ends of the upper track
- Fiberglass reinforced toothed belt links both doors
- Works with the HAWA Junior 80/Z hardware set
- Standard set for door widths of 19 3/4 in to 47 in (500 mm to 1200 mm) each

The HAWA SYMMETRIC 80/Z is an ideal solution for double door boardrooms, restaurants/breakfast rooms, and meeting rooms in residential and commercial applications.

ADVANTAGES AND BENEFITS

- Enables two sliding doors to be opened and closed simultaneously - High-quality carriages enable easy sliding even with just one hand - Robust, maintenance-free design with fiberglass reinforced toothed belt - Doors are installed and the toothed belt assembled from one side - As a complement to the HAWA-Junior 80/Z

INCLUDED IN THIS WEBKIT

	Sales unit
 <p>Hawa Symmetric 80/Z Partial Hardware Set Product # 8920662</p>	Box
 <p>HAWA Groove-Mount Guide Product # 8914540</p>	Length of 1.3 linear meter
 <p>Bottom door stop with centering assembly Product # 8920773174</p>	Bag



HAWA JUNIOR 80/Z Hardware Set with One Track Stoppers
Product # 8911705

Box



HAWA Junior 80 Basic Track
Product # 891853310

Length of 4
linear meter

TECHNICAL SPECIFICATIONS

Product #	WEBKIT1216806
Door Material	Wood
Door Movement	Straight Sliding
Detailed Door Movement	Biparting
Track Mounting	Ceiling Mount
Load Capacity	88.2 to 176 lb*
Door Thickness	1 3/16 to 3 5/32 in*
Roller Type	Axle (Bushing)
Roller Position	Upper
Application	Standard Access Door
Brand	Hawa
Manufacturing Material	Aluminum
Adjustable	Yes
Stopper	Two
Groove Depth	25/32 in*
Number of Doors	2
Door Height	13 ft 1 in*
Groove Width at the Bottom of Door	15/32 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

For use wherever conventional door opening can be cumbersome. For residential use in kitchens, bathrooms, bedrooms, or separating a child's room or two rooms in the house, etc. For commercial use in schools, classrooms, hotel rooms, offices, conference rooms, and more: the possibilities are limited only by your imagination!

INCLUDED PRODUCT(S)

To see the list of included products, please see the datasheet in the Technical Documents section.

IMPORTANT INFORMATION

- Maximum door weight: 80 kg - Door width: 500 mm to 1200 mm - For simultaneous opening of two sliding doors - Must be combined with HAWA-Junior 80/Z to function - Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

PRODUCT PHOTOS

