



AVENTOS HK top Kits

Product # WEBKIT1219849

Door Type Narrow Aluminum-Framed Door (20 mm and Less)

Power Factor 2 266 to 4 200

Finish Light Gray

DESCRIPTION

Effortless opening and smooth closing for pivot-opening doors. Ideal for small cabinets or cupboards. Designed for doors with a maximum width of 70" (1778 mm) and height from 8" to 23" (203 mm to 584 mm).

ADVANTAGES AND BENEFITS

- An innovative mechanism prevents the lever arm from inadvertently folding in for added security.
- Two different opening mechanisms are available: with positioning template or with pre-mounted screws (reversible).

INCLUDED IN THIS WEBKIT

Sales unit



AVENTOS HK top Mechanism

Product # 22K2700

Box



AVENTOS HK top mechanism cover

Product # 22K8000

Set



AVENTOS HS/HL/HK et HK top Hardware Set for Narrow Aluminum Frames

Product # 20S4200A

TECHNICAL SPECIFICATIONS

Product #	WEBKIT1219849
Brand	Blum
Minimum internal depth of the enclosure	7 3/8 in*
Door Height	8 1/16 to 23 5/8 in*
Opening Types	Lift-Up Opening
Door Length	Max. 70 7/8 in*
System Name	Arm
Servo Drive	Not Included
Screw/Nail	Positioning Template
Hinge Opening Angle	+107°

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

INCLUDED PRODUCT(S)

Each set includes: - 1 pair of AVENTOS HK top mechanism - 1 set of covers for AVENTOS HK top opening mechanism - 1 set of fixing brackets

IMPORTANT INFORMATION

Please consult the supplier's documents in order to properly calculate the Power factor (LF) required for your project. Always round up to the highest number for your selection. Formula: (LF) = Cabinet height (KH) mm x Front weight including double handle weight (kg)

PRODUCT PHOTOS

