

Sorry, this product is not available in your region. To find similar products available in your region, click [here](#).



Grant TopLine Straight Sliding Door System

Product # WEBKIT1219944

Track Mounting Ceiling Mount

Load Capacity Max. 150 lb*

Door Thickness Min. 31/32 in*

Overall Length 16 ft*

Soft-Closing No

Number of Doors 2

Packaging format Per unit

DESCRIPTION

Grant TopLine SD, HD and XHD

The Grant TopLine Straight Sliding Door System, featuring Grant TopLine SD, Grant TopLine HD and Grant TopLine XHD, is designed for wood doors weighing up to 500 lb (227 kg) each.

- Precision ball bearing wheel trolleys run on aluminum box tracks
- Silent System soft-close and soft-open mechanism available separately for doors weighing up to 325 lb (147 kg) each.
- Available in 2 packaging formats: kit (hardware and track), bulk (hardware and track selected separately)

These models are designed for commercial and residential use with single, biparting, and bypassing door applications.

ADVANTAGES AND BENEFITS

- Evenly distributes load for maximum performance and durability.
- Requires very little effort to open the door.
- ANSI-BHMA compliant.

INCLUDED IN THIS WEBKIT

Sales unit




Grant TopLine SD Single Upper Track
Product # GT9199841

Length of 16
linear foot



End Cap for Grant SD and HD Track with Fascia
Product # GT9202943

Set



Grant TopLine SD Soft-Close (Silent System)

Product # GT9235608

Set



Grant TopLine Fascia

Product # GT9203746

Length of 16
linear foot



Grant TopLine Ceiling Mount Fascia Clips

Product # GT9203751

Set



Grant TopLine SD Hardware Set

Product # GT9191124

Set

TECHNICAL SPECIFICATIONS

Product #	WEBKIT1219944
Door Material	Wood
Door Movement	Straight Sliding
Detailed Door Movement	Single sliding
Application	Closet and Walk-In Closet, Cabinet, Storage
Brand	Grant Hettich
Door Height	Max. 9 ft 10 in*
Door Width	30 to 94 1/2 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

- For use only in framed installations, do not use in an open-ended application. - For biparting doors, use an additional hardware set. - For bypassing doors, mount parallel tracks. - These instructions assume a properly framed opening with a carefully leveled header. - It is recommended to pre-drill all screws. - Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

PRODUCT PHOTOS

