



HAWA TELESCOPIC Systems: 80/2 - 80/3 - 40/4

Product # WEBKIT1220407

Load Capacity 176 lb*

Door Thickness 1 1/4 to 1 27/32 in*

Overall Length 13 ft 1 in*

Number of Doors 2

Door Width 19 5/8 to 47 1/4 in*

DESCRIPTION

Synchronizes movement of multiple doors

The HAWA TELESCOPIC Systems are a series of pulley systems that work with the Hawa Junior 80/Z system to synchronize the movement of two, three, or four wood doors.

Each can operate multiple doors with or without a recessed bottom guide channel in the floor. We suggest a recessed bottom guide channel in the floor for large doors and heavy traffic areas.

The pulley system includes a fiberglass reinforced toothed belt that resists slipping and stretching.

The following are the telescopic pulley systems to choose from, with the number of doors each operate.

- Hawa Telescopic 80/2 for two wood doors, 176 lb (80 kg) each
- Hawa Telescopic 80/3 for three wood doors, 176 lb (80 kg) each
- Hawa Telescopic 40/4 for four wood doors, 88 lb (40 kg) each

The HAWA TELESCOPIC Systems are ideal for residential and commercial movable partitions in office environments, meeting rooms, multifunctional spaces, restaurants, dining rooms, basement renovations, and exhibit halls.

ADVANTAGES AND BENEFITS

- Enables telescopic opening of two or three sliding doors, or symmetrical opening of four sliding doors.
- Extremely space-saving, as sliding doors only need half the space when open.
- High-quality trolleys enable easy sliding even with just one hand.
- Robust, maintenance-free toothed belt with reinforced fiberglass, ensuring high tensile strength and requiring only minimal extension.
- Suitable even for wide installations - as much as 4 m (13' 1-1/2") - without a bottom guide.

INCLUDED IN THIS WEBKIT

Sales unit




HAWA Groove-Mount Guide
Product # 8914540

Length of 1.3
linear meter



HAWA Junior 80 Basic Track
Product # 891853310

Length of 4
linear meter



Hawa Telescopic 80/2 Partial Hardware Set
Product # 8920657

Box



HAWA JUNIOR 80/Z Hardware Set with One Track Stoppers
Product # 8911705

Box

TECHNICAL SPECIFICATIONS

Product #	WEBKIT1220407
Door Material	Wood
Door Movement	Movable Wall
Detailed Door Movement	Telescoping
Track Mounting	Ceiling Mount
Door Position	Inset/Inlay
Roller Type	Axle (Bushing)
Application	Sliding Wall, Screen Panel
Brand	Hawa
Manufacturing Material	Aluminum
Finish	Satin Aluminum

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

Wherever conventional door opening can be cumbersome. For residential: use system for kitchen, bathroom, bedroom set, make a separation in a child's room or two rooms in the house, etc. For commercial: use the system in schools, classrooms, hotel rooms, office, conference room, in fact, the possibilities are limited only by your imagination.

INCLUDED PRODUCT(S)

To see the list of included products, please see the datasheet in the Technical Documents section.

IMPORTANT INFORMATION

- Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

PRODUCT PHOTOS

