



## Slider S10 Base Cabinet Coplanar System

**Product #** WEBKIT1220479

**Door Width** 18 1/8 to 20 1/8 in\*

**Cabinet Width** 33 7/8 to 38 7/8 in\*

### DESCRIPTION

#### For small-sized wood doors

The Slider S10 Base Cabinet Coplanar System is designed for two wood doors weighing up to 22 lb (10 kg) each.

- Preassembled track series for seven common cabinet widths
- Internal top guide and external bottom running track (no vertical stabilizer hinged bar)
- Double horizontal trolleys
- Integrated soft-close and soft-open mechanism
- Front adjustment of the doors

This coplanar system is ideal for small units installed in kitchen islands, bathroom vanities, or lower storage furniture in offices.

### ADVANTAGES AND BENEFITS

- Great stability - Easy to customize and assemble, no need to drill - Intuitive, smooth, and silent - Extremely strong and durable, stress tested with 100 000 cycles

## INCLUDED IN THIS WEBKIT

**Sales unit**



**Slider S10 Base Track Set**  
Product # 189S10BA0201

Set



**Slider S10 Coplanar System Hardware Set**  
Product # 189S10KIT0101

Set

## TECHNICAL SPECIFICATIONS

Product #	WEBKIT1220479
Door Material	Wood
Door Movement	Coplanar
Load Capacity	Max. 22 lb*
Door Position	Full Overlay
Door Thickness	5/8 to 1 3/16 in*
Application	Furniture
Brand	Salice
Number of Doors	2
Door Height	Max. 31 1/2 in*
Door Installation	Top Hung
Soft-Closing	Yes

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## IMPORTANT INFORMATION

The components must be cleaned using a soft cloth with soap and water. Avoid using products containing solvents and abrasive products. - Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

## DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

## PRODUCT PHOTOS

