



## **Grant E-Series Sliding Door System**

Product # WEBKIT1222404

Detailed Door Movement Single sliding

Overall Length 70 7/8 in\*

Number of Doors 1

#### DESCRIPTION

#### Quick-release top-mount suspension plate

The Grant E-Series Sliding Door System is designed for one or two wood doors with different weight capacities.

Features:

- Choose between two systems:

- A) Grant 75E for min. 3/4 in (19 mm) thick doors weighing up to 75 lb (34 kg)
- B) Grant 150E for min. 1 in (25.4 mm) thick doors weighing up to 150 lb (68 kg)
- Precision ball bearing trolleys
- Vertical adjustment of 1/2 in (2.7 mm)
- Low profile upper track
- Tracks and hardware can also be used in the Grant BF bifold door series

This medium duty system is an ideal solution for commercial and residential applications for closets, storage walls, and cabinets.

### ADVANTAGES AND BENEFITS

- Smooth, quiet, and long-lasting performance - Easily mounted - Minimal headroom required

### INCLUDED IN THIS WEBKIT

Sales unit



Grant 75E Bypassing Hardware Set Product # GT1135333

Set



#### **TECHNICAL SPECIFICATIONS**

Product #	WEBKIT1222404
Door Material	Wood
Door Movement	Straight Sliding
Track Mounting	Ceiling Mount
Load Capacity	22 to 75 lb*
Door Thickness	1 3/8 to 1 25/32 in*
Brand	Grant Hettich
Soft-Closing	No
Grant TopLine Model	Grant 75E
Door Height	Max. 9 ft*
Door Width	23 5/8 to 48 in*

#### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, <u>click here</u>.

### **IMPORTANT INFORMATION**

- Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.

### DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.



# PRODUCT PHOTOS

