



## **HAWA-Concepta Series with Soft-Close Hinges**

Product # WEBKIT1224081

Track Mounting Surface - Inside the Cabinet

Load Capacity 44.1 to 66.1 lb\*

**Number of Doors** 2

Door Height 72 7/8 to 90 1/2 in\*

**Door Width** 11 3/4 to 35 3/8 in\*

Brand Model Hawa Concepta 30

Packaging format Per unit

### **DESCRIPTION**

### Soft-close hinges

The HAWA-Concepta Series with Soft-Close Hinges for four pivot and slide-in pocket door systems for single doors weighing up to 110 lb (50 kg) each. Suitable for the following series:

- HAWA-Concepta 25, for doors weighing up to 55 lb (25 kg) each
- HAWA-Concepta 30, for doors weighing up to 66 lb (30 kg) each
- HAWA-Concepta 40, for doors weighing up to 88 lb (40 kg) each
- HAWA-Concepta 50, for doors weighing up to 110 lb (50 kg) each

#### Features:

- Concealed hinge with soft-close mechanism
- For doors up to 2 in (50 mm) thick
- The mechanism retracts into a small 2 7/8 in (73 mm) parking area
- Single door thicknesses up to 1 1/4 in (30 mm) park into an area 2 3/16 in (55 mm) wide
- Single door thicknesses up to 2 in (50 mm) park into an area 3 5/16 in (83 mm) wide
- Thicker doors possible up to 2 in (50 mm) when not using the connector brackets for decorative cover panels
- Equipped with integrated dampeners for smooth operation
- Included retractable device to assist pulling door into the pocket area
- For technical support and planning tool for drilling patterns for the cabinet and the door, call 800-334-0818 (US) or 844-775-3039 (Canada)

The HAWA-Concepta Series is suitable for commercial and residential applications in kitchens, pantries, closets, laundry rooms, meeting rooms, food and beverage centers, and equipment storage.

### ADVANTAGES AND BENEFITS

- Retractable device - Suitable for cabinet and walk-through doors - Planning tool and installation video available

### **INCLUDED IN THIS WEBKIT**

Sales unit





# Hawa Concepta Bridge Connector Bracket for Two Single Doors Product # 8923223

Box



# **HAWA-Concepta Series with Soft-Close Hinges** Product # 18927649

Set

### TECHNICAL SPECIFICATIONS

Product #	WEBKIT1224081
Door Material	Aluminum/Metal Frame, Wood
Door Movement	Pivot and Slide
Door Position	Inset/Inlay
Door Thickness	3/4 to 1 31/32 in*
Application	Closet and Walk-In Closet, Pantry, Furniture
Brand	Hawa
Door Installation	Side Mount
Packaging Format	Вох
Displayed in These Showrooms	Mississauga, Vancouver

#### **Disclaimer**

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, <u>click here</u>.

### IMPORTANT INFORMATION

- Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant.



### **DISCLAIMER**

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

### PRODUCT PHOTOS













