



## CS Wall Mount Track System

**Product #** WEBKIT1242706

**Load Capacity** 500 lb

**Overall Length** 144 in

**Finish** Bronze Anodized Aluminum

**Soft-Closing** No

**Number of Doors** 2

**Door Width** 24 to 37 in

### DESCRIPTION

#### Silver and bronze finishes

The Cavity Sliders CS Wall Mount Track Systems are for standard sliding wood doors weighing up to 500 lb (227 kg) each.

#### Features:

- Hardware sets without soft-close mechanism for doors weighing up to 200 lb (90 kg) and 500 lb (227 kg)
- Hardware sets with SofStop soft-close mechanisms come in single or twin action for doors weighing up to 176 lb (80 kg), and single action for doors weighing up to 264 lb (120 kg)
- CarriSnap mounting suspension plate at the top of the door for mounting and releasing the upper trolley without tools
- Track and fascia kits for doors 1 3/8 in (35 mm) to 1 3/4 in (45 mm) thick
- Available in silver (clear) and bronze anodized finishes
- Recessed floor guide channels and guide are available for extra wide doors
- Large wheel trolleys with precision ground bearings for smooth running


Ideal for residential, commercial, and institutional projects for a wide variety of applications.

### ADVANTAGES AND BENEFITS

- CarriSnap mounting suspension plate at the top of the door for mounting and releasing the upper trolley without tools
- Available in clear and bronze anodized finishes
- Large wheel trolleys with precision ground bearings for smooth running

## INCLUDED IN THIS WEBKIT

**Sales unit**



### CS CaviTrack Wall Mount Track Kit

Product # TSCTSMBA12135

Length

## CavitySliders CS Hardware Set

Set



Product # DKM0821

## TECHNICAL SPECIFICATIONS

Product #	WEBKIT1242706
Door Material	Wood
Door Movement	Straight Sliding
Detailed Door Movement	Single sliding
Track Mounting	Wall Mount
Door Thickness	1 3/8 to 1 3/4 in
Roller Type	Ball Bearing
Roller Position	Upper
Application	Standard Access Door
Brand	Cavity Sliders
Screw/Nail Included	No
Track type	Box Track
Running Track Fixing	Surface Mount
Manufacturing Material	Aluminum
Door Installation	Top Hung
Door Height	120 in

## DISCLAIMER

Please make sure to read the entirety of the installation manual before proceeding with the installation. #8 screws and appropriate anchors required for installation (not included). A groove is required for the bottom of the door for the floor guide, see instructions. Wear safety gear such as gloves, safety glasses, safety shoes, and ear protection. See instructions for rough opening and other dimensions. Do not exceed stated limitations and parameters. This will cause early wear and performance failure, and will void the warranty. - Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant on this product.

---

## PRODUCT PHOTOS

