



EVO Sliding Door System

Product # WEBKIT1242840

Load Capacity 132 to 176 lb*

Overall Length 78 3/4 in*

Finish Black (90)

Number of Doors 1

Door Width 27 1/2 to 39 3/8 in*

DESCRIPTION

Can be applied to various surfaces

The EVO barn door style sliding system for wood or glass doors for three different weight capacities: 40 kg (88 lb), 60 kg (132 lb), and 80 kg (176 lb).

Features:

- For wood doors 19 mm (3/4 in) to 36 mm (1 3/8 in) thick
- For glass doors 8 mm (5/16 in) to 10 mm (3/8 in) thick
- Available in four finishes: black, chrome, champagne, and titanium
- Three choices of track lengths: 2 m (78 3/4 in), 3 m (118 in), and 4 m (157 in)
- Concealed soft-close mechanisms can be adjusted to different positions
- Bracket support mounts can be adjusted to different positions behind the track
- Choose from two sizes of matching SLIM pull handles with a self-adhesive back that can be applied to smooth surfaces such as wood, laminate, glass, steel, or aluminum
- Smooth operating
- Simple, flexible, and low-cost installation

IMPORTANT: The minimum door width with a soft-close mechanism is 700 mm (27 1/2 in).

Lighting may alter the appearance of some finishes and differ from the published renderings.

Ideal solution for residential and commercial applications for thin and thick doors, feature designer doors, walk-in closets, pantries, and standard access doors to a room.

ADVANTAGES AND BENEFITS

- Available in four finishes: black, chrome, champagne, and titanium
- Three choices of track lengths: 78 3/4 in (2 m), 118 in (3 m), and 156 in (4 m)
- Concealed soft-close mechanisms can be adjusted to different positions
- Bracket support mounts can be adjusted to different positions behind the track
- Matching pull handle SLIM with self-adhesive back can be applied to different surfaces

INCLUDED IN THIS WEBKIT

Sales unit



SLIM Door Pull with Self-Adhesive Back

Product # 89SLIM3090



EVO Track Set
Product # 89127B21090

Set



EVO Hardware Sets
Product # 891271990

Set

TECHNICAL SPECIFICATIONS

Product #	WEBKIT1242840
Door Material	Wood, Glass
Door Movement	Straight Sliding
Detailed Door Movement	Single sliding
Track Mounting	Wall Mount
Door Thickness	5/16 to 1 13/32 in*
Roller Type	Premium Ball Bearing
Roller Position	Upper
Application	Standard Access Door, Barn Door
Screw/Nail Included	Yes
Height Clearance	7 17/32 in*
Running Track Fixing	Bracket
Manufacturing Material	Aluminum
Adjustable	Yes
Soft-Closing	Yes
Soft-Close Type	One-Way Operation
Displayed in These Showrooms	Toronto
Style	Barn Door
Groove Depth	1/2 in*
Groove Needed for Guiding System	Yes
Door Projection	3 5/32 in*
Door Installation	Top Hung
Door Height	Max. 8 ft 6 in*
Groove Width at the Bottom of Door	15/32 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

- IMPORTANT: The minimum door width with soft-close mechanism is 27 1/2 in (700 mm). - Please make sure to read the entirety of the installation manual before proceeding with the installation. - Wear safety gear such as gloves, safety glasses, safety shoes, and ear protection. - Every fastener used to attach the track to the wall must be fastened securely into a structural surface. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant on this product. - Do not exceed stated limitations and parameters. This will cause early wear and performance failure, and will void the warranty.

APPLICATION

- For wood and glass doors

DISCLAIMER

Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation.

PRODUCT PHOTOS







