



RO 44 Sliding Door System

Product # WEBKIT1242903

Number of Doors 2

Overall Length Max. 78 3/4 in*

Door Width 19 5/8 to 39 3/8 in*

DESCRIPTION

Concealed and adjustable

The RO 44 Sliding Door System is for medium to tall wood cabinet doors for bypassing applications with a door weight of 132 lb (60 kg). Versatile system that can be used in closets and cabinets.

Features:

- For wood doors 5/8 in (15 mm) to 3/4 in (20 mm) thick
- Operation runs on surface mount type RM 022 dual bottom track and guided by RM 030 upper dual upper guide track
- Includes upper track stopper with retaining device to resist door bounce back
- Simple and flexible installation
- Thicker doors are possible if the bottom wheels are offset on the door and the top of the door is rebated around the upper guide track

IMPORTANT: For optimal performance, make sure the dimensions of the door are balanced. It is suggested to build the door height 3 times or less than the width of the door (max. 1:3 ratio).

Ideal for residential and commercial applications for medium to tall cabinet doors for storage units, office furniture, bookshelves, entertainment units, closets, and wardrobes/armoires.

ADVANTAGES AND BENEFITS

- Concealed hardware - For cabinets and closets - For wood doors 5/8 in (15 mm) to 3/4 in (20 mm) thick - Surface mount tracks - Simple and flexible direct mount installation

INCLUDED IN THIS WEBKIT

Sales unit



Door Straightener/Stiffener

Product # 189BR208B0010

Bag

Type RM 022 Dual Bottom Track

Product # 189RM022A210

Length





RO 44 Hardware Set for One Door

Product # 8761RO44

Set



Type RM 030 Dual Upper Guide Track

Product # 1892197A210

Length

TECHNICAL SPECIFICATIONS

Product #	WEBKIT1242903
Door Material	Wood
Door Movement	Straight Sliding
Detailed Door Movement	Bypassing
Track Mounting	Floor Mount
Load Capacity	132 lb*
Door Thickness	19/32 to 25/32 in*
Application	Closet and Walk-In Closet, Wardrobe, Furniture, Cabinet
Door Height	31 7/8 to 96 in*
Finish	Silver

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

IMPORTANT: For optimal performance, make sure the dimensions of the door are balanced. It is suggested to build the door height 3 times or less than the width of the door (max. 1:3 ratio). - Use metric dimensions for greater accuracy during installation. - Please make sure to read the entirety of the installation manual before proceeding with the installation. - Wear safety gear such as gloves, safety glasses, safety shoes, and ear protection. - Every fastener used to attach the track to the wall must be fastened securely into a structural surface. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant on this product. - Do not exceed stated limitations and parameters. This will cause early wear and performance failure, and will void the warranty.

DISCLAIMER

Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation.

PRODUCT PHOTOS



