



SLIDE 40 Sliding Door System

Product # WEBKIT1242997

Overall Length 78 3/8 in*

Soft-Closing No

Door Width 23 7/8 to 39 in*

DESCRIPTION

Concealed low profile soft-close mechanisms

The SLIDE 40 sliding cabinet wood door system with concealed low profile for inset applications with a door weight capacity of 88 lb (40 kg) each.

Features:

- For wood doors 3/4 in (18 mm) to 1 in (25 mm) thick
- 2 recessed low profile soft-close mechanisms
- Rollers are equipped with anti-derailment springs
- Select from two recessed track lengths: 78 1/4 in (1.99 m) and 117 5/8 in (2.99 m)
- Simple and flexible installation

IMPORTANT: The minimum door width with soft-close mechanism is 27 1/2 in (700 mm).

Cut a groove for the track 19/32 in (15 mm) wide x 15/32 in (12 mm) deep. Use metric dimensions for greater accuracy during installation.

Ideal solution for office furniture, bookcases/libraries, kitchen cabinets, closets, wardrobes/armoires, and other millwork applications.

ADVANTAGES AND BENEFITS

- 2 recessed low profile soft-close mechanisms
- Rollers are equipped with anti-derailment springs
- Select from two recessed track lengths: 78 1/4 in (1.99 m) and 117 5/8 in (2.99 m)
- Simple and flexible installation

INCLUDED IN THIS WEBKIT

Sales unit

SLIDE 40 Single Recessed Track

Product # 189TK11092L210

Length



SLIDE 40 Basic Hardware Set

Product # 189K3600

Set



TECHNICAL SPECIFICATIONS

Product #	WEBKIT1242997
Door Material	Wood
Door Movement	Straight Sliding
Detailed Door Movement	Bypassing
Track Mounting	Recessed - Inside the Cabinet
Load Capacity	88.2 lb*
Door Position	Inset/Inlay
Door Thickness	23/32 to 31/32 in*
Roller Position	Lower
Application	Closet and Walk-In Closet, Wardrobe, Furniture, Cabinet
Number of Doors	2
Door Height	Max. 96 in*
Door Installation	Bottom Running
Manufacturing Material	Aluminum

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

- IMPORTANT: The minimum door width with soft-close mechanism is 27 1/2 in (700 mm). - Use metric dimensions for greater accuracy during installation. - Please make sure to read the entirety of the installation manual before proceeding with the installation. - Wear safety gear such as gloves, safety glasses, safety shoes, and ear protection. - Every fastener used to attach the track to the wall must be fastened securely into a structural surface. - Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant on this product. - Do not exceed stated limitations and parameters. This will cause early wear and performance failure.

DISCLAIMER

Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation.

PRODUCT PHOTOS

