



HAWA Porta 60/100 HMD System

Product # WEBKIT1243365

Detailed Door Movement Biparting

Load Capacity 134 to 220 lb*

Number of Doors 2

Door Width 33 1/8 to 35 3/8 in*

DESCRIPTION

Low profile upper track

The HAWA PORTA 60/100HMD is a low-profile sliding system for wood doors weighing up to 60 kg or 100 kg each.

- Rebate/mortise mount suspension plate for the top of the door
- Low profile upper track for low overhead clearance
- Integrated track stopper with adjustable retaining device to resist door bounce back
- Mount track directly to the wall for simple installation
- Smooth and quiet premium ball bearing trolleys
- Automatic soft close mechanism available, sold separately
- Soft close mechanism can be added or removed after the track is installed

An ideal solution for premium commercial and residential projects, single door openings, room dividers, and applications with low headroom.

IMPORTANT: Use metric dimensions for greater accuracy during installation. Cut a groove 12 x 16 mm at the bottom of the door for floor guide. For door widths greater than 1200mm we suggest a bottom guide rail.

ADVANTAGES AND BENEFITS

- Minimal installation height - Track mounts flush with ceiling - Smooth glide thanks to ball-bearing rollers - Continuous height adjustment - Adjustable stopping force

INCLUDED IN THIS WEBKIT

Sales unit



Integrated Soft-Close System for Sliding Door

Product # 893102071

Box



HAWA PORTA 60 HM Hardware Set

Product # 893133072

Box



Clip Panel, Aluminum, 3.5 m
Product # 893113350

Length of 3.5
linear meter



HAWA PORTA Plastic End Cap
Product # 893131072

Bag



HAWA PORTA Wall Mount Track
Product # 893112350

Length of 3.5
linear meter

TECHNICAL SPECIFICATIONS

Product #	WEBKIT1243365
Door Material	Wood
Door Movement	Straight Sliding
Track Mounting	Wall Mount
Door Position	In Front of Wall
Door Thickness	1 3/16 to 1 25/32 in*
Roller Type	Ball Bearing
Roller Position	Upper
Application	Closet and Walk-In Closet, Storage, Screen Panel
Brand	Hawa
Overall Length	11 ft 5 in*
Manufacturing Material	Aluminum
Finish	Satin Aluminum
Soft-Closing	Yes
Stopper	Two
Groove Depth	5/8 in*
Groove Needed for Guiding System	Yes
Milling Depth	29/32 in*
Milling	23/32 in*
Door Height	Max. 8 ft 10 in*
Groove Width at the Bottom of Door	15/32 in*
Brand Model	Hawa Porta

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

- Wooden doors - Private living areas - Private and public office areas - Projects - Individualized interior design

IMPORTANT INFORMATION

For smoother opening and closing, add the following items to your order: 893102071 and 89311407. The distance between the bearings must be 570 mm on center. - Maximum door width: 1.6 m - Maximum height of the door: 2.7 m - Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation. - Always remove debris/dust/residue (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant on this product.

DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

PRODUCT PHOTOS

