



Kits AVENTOS HF Lift System

Product # WEBKIT1244153

Door Type Wide Aluminum-Framed Door

Power Factor 5 351 to 9 575

Door Height 27 5/8 to 29 7/8 in*

DESCRIPTION

Provides effortless opening and smooth, silent closing for folding doors. Mechanism designed for bi-fold doors from 18-7/8" to 41,02" in height and from 15" to 72" in width. The handle can be installed anywhere on the 2 doors. Easy to install and to adjust. Clip to restrict opening angle is also available.

ADVANTAGES AND BENEFITS

- BLUMOTION device integrated for silent, effortless closing.
- The door stops at any opening position for direct, ergonomic access to the handle.
- The central hinge disconnects under tension for finger safety and protection.
- Provides unparalleled flexibility and the ability to combine fronts of unequal heights.

INCLUDED IN THIS WEBKIT

	Sales unit
 <p>Telescopic Arm Set HF Product # 20F3800</p>	Box
 <p>Bifold Lift Mechanism AVENTOS HF Product # 20F2500N5</p>	Box
 <p>AVENTOS HF Hardware Set for Wood or Wide Aluminum Frames Product # 78Z5530TA8</p>	Bag

REQUIRED PRODUCTS

Requires ONE of the following products

	Sales unit
 <p>AVENTOS HF mechanism cover Product # 20F8020105 Finish: Light Gray</p>	Box
OR	
 <p>AVENTOS HF mechanism cover Product # 20F8020108 Finish: Dark Gray</p>	Box
OR	
 <p>AVENTOS HF mechanism cover Product # 20F802030 Finish: White</p>	Box

TECHNICAL SPECIFICATIONS

Product #	WEBKIT1244153
Opening Types	Folding Opening
Minimum internal depth of the enclosure	11 in*
Brand	Blum
Servo Drive	Not Included

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

High upper-cabinet doors in modern and contemporary kitchens.

IMPORTANT INFORMATION

- We recommend the use of 3 hinges for cabinet widths of 1,200 mm and more (47-1/4") or for door weights of 12 kg and more, and the use of 4 hinges for cabinet widths of 1,800 mm and more (70-13/16") or for door weights of 20 kg and more. - For doors with frames less than 22 mm or between 22 and 47 mm in width, we recommend the use of mounting brackets for narrow frames.

PRODUCT PHOTOS





www.richelieu.com

www.richelieu.com

www.richelieu.com