



## Kits AVENTOS HF Lift System

**Product #** WEBKIT1244174

**Door Type** Wide Aluminum-Framed Door

**Power Factor** 5 351 to 9 575

**Door Height** 39 3/8 to 41 in\*

### DESCRIPTION

Provides effortless opening and smooth, silent closing for folding doors. Mechanism designed for bi-fold doors from 18-7/8" to 41,02" in height and from 15" to 72" in width. The handle can be installed anywhere on the 2 doors. Easy to install and to adjust. Clip to restrict opening angle is also available.

### ADVANTAGES AND BENEFITS

- BLUMOTION device integrated for silent, effortless closing. - The door stops at any opening position for direct, ergonomic access to the handle. - The central hinge disconnects under tension for finger safety and protection. - Provides unparalleled flexibility and the ability to combine fronts of unequal heights.

## INCLUDED IN THIS WEBKIT

**Sales unit**



**Telescopic Arm Set HF**  
Product # 20F3900

Box



**Bifold Lift Mechanism AVENTOS HF**  
Product # 20F2500N5

Box



**AVENTOS HF Hardware Set for Wood or Wide Aluminum Frames**  
Product # 78Z5530TA8

Bag

## REQUIRED PRODUCTS

Requires ONE of the following products

|   |   | Sales unit |
|---|---|------------|
|   | <b>AVENTOS HF mechanism cover</b><br>Product # 20F8020105<br>Finish: Light Gray | Box        |
|   | OR  |            |
|   | <b>AVENTOS HF mechanism cover</b><br>Product # 20F8020108<br>Finish: Dark Gray  | Box        |
|   | OR  |            |
|  | <b>AVENTOS HF mechanism cover</b><br>Product # 20F802030<br>Finish: White       | Box        |

## TECHNICAL SPECIFICATIONS

|   |                 |
|---|-----------------|
| Product #                               | WEBKIT1244174   |
| Opening Types                           | Folding Opening |
| Minimum internal depth of the enclosure | 11 in*          |
| Brand                                   | Blum            |
| Servo Drive                             | Not Included    |

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## APPLICATION

High upper-cabinet doors in modern and contemporary kitchens.

## IMPORTANT INFORMATION

- We recommend the use of 3 hinges for cabinet widths of 1,200 mm and more (47-1/4") or for door weights of 12 kg and more, and the use of 4 hinges for cabinet widths of 1,800 mm and more (70-13/16") or for door weights of 20 kg and more. - For doors with frames less than 22 mm or between 22 and 47 mm in width, we recommend the use of mounting brackets for narrow frames.

## PRODUCT PHOTOS



