



AVENTOS HL Kits

Product # WEBKIT1244224

Door Type Wide Aluminum-Framed Door

Door Height 15 3/4 to 19 5/8 in*

Door Weight 3.86 to 6.83 lb*

DESCRIPTION

Effortless opening and smooth closing for parallel-opening doors. Designed for doors from 15" to 72" in width and from 11-13/16" to 22-13/16" in height. Easy installation and adjustment. The handle can be installed without any height restrictions.

ADVANTAGES AND BENEFITS

- Integrated BLUMOTION device for soft closing - Parallel opening for complete clearance and ease of access

INCLUDED IN THIS WEBKIT

Sales unit



Hardware Bracket Set for Wood and Wide-Framed Aluminum Doors

Product # 20S4200

Pair



AVENTOS Arm Set HL without SERVO-DRIVE

Product # 20L380006

Box



Oval Stabilizer Bar

Product # 20Q1061UA






AVENTOS Lift Mechanism HL

Product # 20L2300N5

Box

REQUIRED PRODUCTS

Requires ONE of the following products

		Sales unit
	AVENTOS HL mechanism cover Product # 20L8020105 Finish: Light Gray	Box
	OR	
	AVENTOS HL mechanism cover Product # 20L8020108 Finish: Dark Gray	Box
	OR	
	AVENTOS HL mechanism cover Product # 20L802030 Finish: White	Box

TECHNICAL SPECIFICATIONS

Product #	WEBKIT1244224
Brand	Blum
Opening Types	Parallel Opening
Minimum internal depth of the enclosure	11 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

Upper cabinets. Ideal for concealing appliances such as microwaves, and perfectly suited to house items you may occasionally wish to display.

IMPORTANT INFORMATION

For doors with frames less than 22 mm or between 22 and 47 mm in width, we recommend the use of mounting brackets for narrow frames. - For doors more than 1219 mm in width, use two stabilizer rods and one connection piece kit.

PRODUCT PHOTOS



