



Kits AVENTOS HS Lift System

Product # WEBKIT1244258

Door Type Wood Door

Door Height 16 to 16 3/4 in*

Door Weight 19.3 to 27 lb*

System Name C

DESCRIPTION

Effortless opening and smooth closing for up-and-over lift doors. Adapted for door widths from 15" to 72" and heights from 13-3/4" to 31-1/2". Easy to install and to adjust. Offers the possibility of using 2 shelves.

ADVANTAGES AND BENEFITS

- Integrated BLUMOTION device for soft closing - 3 lift mechanisms and 1 arm set covering various door weights and heights - The door swings up and over, reducing the risk of obstruction with the crown molding on the top of the cabinet; see clearance space in the technical drawings.

INCLUDED IN THIS WEBKIT

Sales unit



Cross Stabilizer Bar For AVENTOS HS

Product # 20Q1061UN



Hardware Bracket Set for Wood and Wide-Framed Aluminum Doors

Product # 20S4200

Pair



Arms for AVENTOS HS without SERVO-DRIVE

Product # 20S350006

Box



Mechanism for AVENTOS HS

Product # 20S2C00N5

Box

TECHNICAL SPECIFICATIONS

Product #	WEBKIT1244258
Opening Types	Up and Over Opening
Minimum internal depth of the enclosure	10 7/8 in*
Brand	Blum
Servo Drive	Not Included

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

Ideal for upper cabinets with large fronts. Perfectly suited for contemporary kitchens.

IMPORTANT INFORMATION

- For doors with frames less than 22 mm or between 22 and 47 mm in width, we recommend the use of mounting brackets for narrow frames. - For doors more than 1219 mm in width, use two stabilizer rods and one connecting piece kit.

PRODUCT PHOTOS



