



CINETTO PS66 Pocket Door System

Product # WEBKIT1245616

Opening Remote / Right-Hand Opening

DESCRIPTION

No visible tracks

The CINETTO PS66 Pocket Door System is an innovative sliding door mechanism with fully concealed tracks for a single wood door with a maximum weight of 50 kg (110 lb). Includes dampers to cushion stop the door for a soft close action. The unique Y-mechanism retracts the door into a pocket area straight and prevents the door from racking.

A vertical profile supports the along door vertical door edge for door thickness from 25 to 40 mm (1 to 1-1/2 in) and height from 2100 to 2400 mm (83 to 94 in). Special order systems are available upon request for tall doors up to 3000 mm (118 in) and glass doors 8 mm (5/16 in) thick. Consult with Richelieu Sliding Door Specialist.

Installation is flexible and ideal for applications without ceiling support and adaptable for a wall, cabinet, and other millwork. The pocket area is intended to be covered by panel boards. Ideal for Office Cubicles; Millwork, and to create kitchen walk-in pantries and closets; and standard passage doors.

The B-moved electric system can be bolt-on and concealed within the pocket area to operate the door hands-free with a remote; WAVE proximity sensor (sold separately). Compatible with Smart Home devices, cellphone AP's, and Voice Control devices (consult a certified electrician).

IMPORTANT: Use metric dimensions for greater accuracy during installation.

ADVANTAGES AND BENEFITS

- No visible tracks - Can be installed where there is no ceiling - Hands-Free B-moved electric motor (sold separately)

INCLUDED IN THIS WEBKIT


Sales unit



B-Moved Control Unit with Remote

Product # 189CUPS66


Set



PS66 Sliding Mechanism

Product # 189PS66MD240R

Set



PS66 Wood Door Assembly Kit

Product # 189PS66W240R

Set



B-Moved Motion Transmission Bar

Product # 189PS66BEMR

TECHNICAL SPECIFICATIONS

Product #	WEBKIT1245616
Door Material	Wood
Door Movement	Pocket Door, Straight Sliding
Load Capacity	44.1 to 110 lb*
Door Thickness	31/32 to 1 9/16 in*
Application	Closet and Walk-In Closet, Pantry, Standard Access Door, Pocket Door
Brand	CINETTO
Compatible with	B-MOVE
Soft-Closing	Yes
Number of Doors	1
Door Height	82 5/8 to 94 1/2 in*
Door Width	23 5/8 to 39 3/8 in*
Brand Model	Cinetto PS66

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

Use metric dimensions for greater accuracy during installation. Please make sure to read the entirety of the installation manual before proceeding with the installation. Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. Never spray lubricant on this product. Do not exceed stated limitations and parameters. This will cause early wear and performance failure. When using the B-moved system, consult with a certified electrician before installation to ensure you have a proper power source.

DISCLAIMER

Wear safety gear such as gloves, safety glasses, safety shoes, and ear protection. See instructions for rough opening and other dimensions. Do not exceed stated limitations and parameters. This will cause early wear and performance failure and void the warranty.

- Pictures provided for visual reference only: actual product may vary.
- All required hardware should be ordered and obtained before initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout.
- Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice.
- The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers.
- Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation.
- Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system.
- Never spray lubricant on this product.

PRODUCT PHOTOS

