



TERNO ACCORDION End Fold Door System

Product # WEBKIT1245619

Overall Length 48 in*

Bottom Guide No

Number of Doors 2

Door Width 12 to 24 in*

DESCRIPTION

Adjustable

The TERNO ACCORDION End Fold Door System for multiple wood doors weighing up to 40 kg (88 lb) each.

Features:

- Versatile folding door system for 2 to 6 door panels
- First panel is anchored securely by an upper pivot mounted in the track and a lower pivot mounted to the door jamb
- Hardware can be surface mounted to the door
- Top and bottom surface mount scissor-type hinges
- No bottom guide channel necessary for 2 folding panels less than 610 mm (24") wide each
- Use a floor guide channel for door panel widths greater than 610 mm (24")
- For extra wide door panels 752 to 914 mm (30" to 36"), use concealed 3D or SOSS hinges (do not use the standard scissor-type hinges)
- Simple to install and easy to adjust

An ideal solution for residential and commercial applications. Perfect for dividing a room or closing a large opening. For meeting rooms, office spaces, classrooms, multi-purpose rooms, common areas/foyers in condominiums, restaurants and kitchens and dining rooms.


IMPORTANT: Use metric dimensions for greater accuracy during installation. There will be extra unused parts for some end-folding door configurations. Bottom guide is required when folding 3 or more panels to one side. Do not use scissor type hinges when folding 3 panels or more.

ADVANTAGES AND BENEFITS

- Hardware can be surface mounted to the door - Top and bottom scissor type hinges - Simple to install and easy to adjust - First panel is anchored securely by an upper pivot mounted in the track and a lower pivot mounted via a bracket in the door jamb - Concealed 3D adjustable hinges for 3 and more folding panels

INCLUDED IN THIS WEBKIT


Sales unit



TERNO ACCORDION FOLDING Hardware Set

Product # 89K02251

Set



Single Upper Running Track Type 1280
Product # 891280A210

Length of 2
linear meter

TECHNICAL SPECIFICATIONS

Product #	WEBKIT1245619
Door Material	Wood
Door Movement	Folding
Detailed Door Movement	End folding, Bifolding
Track Mounting	Ceiling Mount
Load Capacity	88.2 lb*
Door Thickness	1 3/16 to 1 25/32 in*
Brand	Terno
Door Installation	Top Hung
Door Height	39 3/8 to 106 in*
Brand Model	Terno Accordion

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

- Room divider

IMPORTANT INFORMATION

- Bottom guide is required when folding 3 or more panels to one side - Pictures provided for visual reference only: actual product may vary - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liability for results obtained through improper use or installation. - Always remove debris/dust/residue (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never use spray lubricant.

DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

PRODUCT PHOTOS



89K02251

L	

