



COMFORT 240 Soft Close Series

Soft-Close Type

1 soft close

2 Soft Close

DESCRIPTION

With Activator

The COMFORT 240 Soft Close series is for the RO 44 sliding door system for wood door weight capacity 15 - 40 kg (33 - 88 lbs) each. Simple installation. The soft close mechanism is concealed inside the ceiling with the upper guide tracks RM-030 and RM-055. The activator is included and mounted to the top of the door. Choose from two types of sets, single or double soft close mechanisms.

IMPORTANT: The recommended minimum door width is 700 mm (27 1/2 in). For optimal performance, balance the dimensions of the door. It is suggested to build the door height three times or less than the width of the door (max. 1:3 ratio).

ADVANTAGES AND BENEFITS

* Concealed direct mount soft close mechanism * Includes activator

AVAILABLE PRODUCTS

Product #	Soft-Close Type
1896770	1 soft close
1896771	2 Soft Close

TECHNICAL SPECIFICATIONS

Door Material	Wood
Load Capacity	15 to 40 kg
Manufacturing Material	Plastic
Width	40 mm
Door Width	700 to 1 219 mm
Door Thickness	20 mm
Product type	Stopper, Soft-Close
Overall Length	250 mm
Compatible with	RO 44
Soft-Closing	Yes
Overall Height	30 mm
Application	Closet and Walk-In Closet, Wardrobe, Pantry
Detailed Door Movement	Single sliding, Bypassing
Door Movement	Straight Sliding

INCLUDED PRODUCT(S)

* 1 soft close mechanism * 1 activator

IMPORTANT INFORMATION

IMPORTANT: For optimal performance, balance the dimensions of the door. It is suggested to build the door height three times or less than the width of the door (max. 1:3 ratio). * Use metric dimensions for greater accuracy during installation. * Please make sure to read the entirety of the installation manual before proceeding with the installation. * Use metric dimensions for greater accuracy during installation * wear safety gear such as gloves, safety glasses, safety shoes, and ear protection * Every fastener used to attach the track to the wall must be fastened securely into a structural surface. * Always remove debris/dust/residues (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. * Never spray lubricant on this product. * Do not exceed stated limitations and parameters. This will cause early wear and performance failure.

APPLICATION

Cabinet, Furniture, Bookshelf, Wardrobe/Armoire, Closets

DISCLAIMER

By accessing or referring to this document, or by using any of Richelieu's websites, you accept all applicable terms as they apply from time to time. This legal disclaimer is in no way limited or altered by any other terms or conditions. Richelieu may change said terms at its discretion and without prior notice. A version of the most current terms will always be available on Richelieu's website. The preceding information and technical documentation, information, or recommendations issued by Richelieu verbally or in writing is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for use or application are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representation of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for particular purpose, non-infringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark, and designs. Any trademarks identified herein are trademarks of the Richelieu group of companies. Richelieu assumes no risk and shall not be subject to any liability for damages or loss resulting from the specific use or application made of the product. Richelieu's liability for any claim, whether based on breach of contract, negligence, or infringement of any rights of any party relating to the product shall not exceed the price paid for said products. In no event shall Richelieu be liable for any special, incidental, or consequential damages (including loss of use, loss of profit, and claims of third parties) however caused, whether by the negligence of Richelieu or otherwise. Products returned for warranty purposes shall be subject to Richelieu's then applicable Return Policy.

PRODUCT PHOTOS



CODE
1896770 = 15 - 40 kg



CODE
1896771 = 15 - 40 kg