



## Piston Mechanism

### Door Type

Narrow  
Aluminum-  
Framed Door  
(20 mm and  
Less)

Wide  
Aluminum-  
Framed Door  
/ Wood Door

## DESCRIPTION

Mechanism for lift-up doors. Opening is activated by a gas piston for smooth movement.

## ADVANTAGES AND BENEFITS

- Weight capacity: max. 12 kg (26.45 lb.) - Opening angle: 80° to 100° - Can be installed on wood or aluminum-framed doors (brackets not included).

## AVAILABLE PRODUCTS

Product #	Door Type
<b>WEBKIT10874</b>	Narrow Aluminum-Framed Door (20 mm and Less)
<b>WEBKIT10873</b>	Wide Aluminum-Framed Door / Wood Door

## TECHNICAL SPECIFICATIONS

Type of Opening	Lift-Up Opening
Door Height	15 3/4 to 23 5/8 in*
Door Length	17 3/4 to 27 1/2 in*
Opening Types	Lift-Up Opening
Load Capacity	6.61 to 17.6 lb*

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## APPLICATION

Multiple applications including kitchens, closets, offices, and more.

## IMPORTANT INFORMATION

- 100° hinges are required for installation (not included). - Note: for doors less than 3 kg, use 1 piston; for doors more than 3 kg, use 2 pistons. - 2 pistons are required for doors over 750 mm (29-1/2") in height.

## PRODUCT PHOTOS

