



SpeedBrace Countertop Brace - White

Projection - Overall Dimensions

| 8 in | 12 in | 18 in | 24 in | 28 in |
|------|-------|-------|-------|-------|
| | | | | |

Height - Overall Dimensions

| 5 in 8 in | 15 in | 21 in |
|-----------|-------|-------|
|-----------|-------|-------|

DESCRIPTION

For precise alignment, the steel SpeedBrace countertop brace system is perfect. Can be used for office desks.

ADVANTAGES AND BENEFITS

- Uses 1 1/2 in (38.1 mm) x 3/4 in (19.05 mm) cleat system - Double notch system for fast and easy alignment - Wire management. No kicker. - Load capacity: 1000 lb (453.59 kg)/pair on 16 in (406.4 mm) centers - 12-gauge - 1 1/2 in (38.1 mm) x 1 1/2 in (38.1 mm) notch in corner for installation against 2 x 2 wall cleat - 5 in (127 mm) x 8 in (203.2 mm) Speedbrace has 1 1/2 in (38.1 mm) x 1/2 in (12.7 mm) notch for installation with 1 x 2 wall cleat - Pass-through holes for cables and cords

AVAILABLE PRODUCTS

| Product # | Projection - Overall Dimensions | Height - Overall Dimensions |
|-----------|---------------------------------|-----------------------------|
| 918050830 | 8 in | 5 in |
| 918081230 | 12 in | 8 in |
| 918151830 | 18 in | 15 in |
| 918212430 | 24 in | 21 in |
| 918212730 | 28 in | 21 in |

TECHNICAL SPECIFICATIONS

| Maximum Load Capacity per Shelf | 500 lb |
|---------------------------------|--------|
| Material | Steel |
| Color/Finish | White |

IMPORTANT INFORMATION

Sold by the unit.



PRODUCT PHOTOS



