



## Painter's Ultra Siliconized Acrylic Latex

### Finish/Color

Clear  
Transparent

Off White

### DESCRIPTION

#### Contains additional silicone substances

Richelieu® Painter's ultra-siliconized acrylic latex is a moderately priced caulking material with added silicone for superior adhesion and strength. When exposed to the atmosphere, cures to form a continuous monolithic seal ideally suited for interior or exterior applications.

Richelieu® Painter's Ultra is an excellent all-purpose sealant for cracks and joints and exhibits good adhesion to the full range of construction substrates including wood, concrete, metal, glass, stone, brick, stucco and marble. This sealant is also recommended for sealing interior joints between walls and panels, around door frames and baseboards, and joints between bathroom fixtures and walls.

### ADVANTAGES AND BENEFITS

- Adheres to many construction substrates. - Ideal for walls, panels, door frames, baseboards, etc. - An excellent all-purpose sealant for cracks and joints. - Cures to rubbery seal that withstands joint movement of 50%, 18% compression, 18% extension. - Ready to use: no mixing required. - Long-lasting: The life expectancy of cured sealant in place is approximately 20 years. - Paintable within 2 to 6 hours after application depending on weather conditions - Will not sag or run when applied on vertical joints, if applied according to directions. - Non-staining: resists chemical and solvent damage. - Solvent-free: cleans up with water. Beads may be tooled with soapy water. - Dirt: Resists dirt pick-up once cured.

### AVAILABLE PRODUCTS

Product #	Finish/Color
94150111	Clear Transparent
94150130	Off White

## TECHNICAL SPECIFICATIONS

<b>Recommended Use</b>	Interior, Exterior, Bathroom / Kitchen, Door and Window
<b>Color on Application</b>	White
<b>Base</b>	Siliconized Acrylic Latex
<b>Volume</b>	10.1 oz*
<b>Packaging Specifications</b>	Plastic Cartridge
<b>Brand</b>	Richelieu
<b>Features</b>	Water Resistant, Without Solvent, Superior Bond, Wash with Water, Paintable
<b>Freeze/Thaw Stability</b>	Stable
<b>Standards and Certifications</b>	ASTM C834, LEED 4.1, LEED 5.1

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## APPLICATION

Richelieu® 941501 will fill cracks and joints up to 25.4 mm (1" ) wide by 12.7 mm (1/2" ) deep in a single application. Also excellent for filling imperfect mitres on window and door trims that are to be painted, giving a more professional look to the finished job.

## IMPORTANT INFORMATION

Exclusion from responsibility: The preceding information as well as any technical recommendation given in writing, verbally or based on tests are provided to the best of our knowledge. However, they are non-binding recommendations only and do not affect your responsibility to determine the correctness of given recommendations and suitability of the product for your particular purposes. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore fall exclusively in your area of responsibility. Sales of our products are effected according to our most updated General Sales and Delivery Conditions

## PRODUCT PHOTOS

---

