



Jowatherm 286 Hot Melt Adhesive Cartridge

Filler Agent

- With
- Without

Finish/Color

- Natural
- White

Weight

- 26 lb
- 35 lb

Viscosity

- 50 000 - 100 000 cps
- 60 000 - 120 000 cps

DESCRIPTION

Hot melt adhesive cartridge with high heat resistance and good cold flexibility.

ADVANTAGES AND BENEFITS

- Excellent color and heat stability - High heat resistance - Good cold flexibility.

AVAILABLE PRODUCTS

Product #	Filler Agent	Finish/Color	Weight	Viscosity
JW28680	With	Natural	35 lb	60 000 - 120 000 cps
JW28681	With	White	35 lb	60 000 - 120 000 cps
JW28630	Without	Natural	26 lb	50 000 - 100 000 cps

TECHNICAL SPECIFICATIONS

Type	Cartridges
Line speed (/minute)	32 ft 9 in to 197 ft*
Adhesive for use with	Thin PVC and ABS edgbanding, Thick PVC and ABS edgebanding, Solid wood edgebanding, Multi-layered 1, 1.5, 2, 3 mm edgebanding, Backed thin wood edgebanding, Laminate, Resin-embedded paper
Working Temperature	180 °C to 200 °C
Brand	Jowat
Features	High Heat Resistance
Base	Ethylene Vinyl Acetate

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

Hot melt for automatic edgebanding. Suitable for: - Solid wood - Primed HPL - Veneer - PVC - Resinated paper

IMPORTANT INFORMATION

It is highly recommended to consult your sales representative or a technical expert before purchasing a new edgebanding glue.

PRODUCT PHOTOS

