



## Titebond III Ultimate Wood Glue

### Volume

16 oz	32 oz	1 gal.	2.15 gal.	5 gal.
55 gal.				

### DESCRIPTION

A revolutionary technology offering the best performance in wood adhesives. Meets ANSI/HPVA Type I water-resistance standards and offers superior bond strength, longer open assembly time, and a lower application temperature.

Safer to use than traditional waterproof wood glues, Titebond III is non-toxic, solvent-free, and cleans up with water. Provides strong initial tack, sands easily without softening, and is FDA approved for indirect food contact (e.g. cutting boards). The ultimate in wood glues, ideal for both interior and exterior applications.

### ADVANTAGES AND BENEFITS

- Waterproof formula that cleans up with water - Superior strength - Strong initial tack - Designed for interior and exterior applications - Longer open assembly time - Lower application temperature - Unaffected by finishes

### AVAILABLE PRODUCTS

Product #	Volume
15001414	16 oz
15001415	32 oz
15001416	1 gal.
150014109	2.15 gal.
15001417	5 gal.
15001418	55 gal.

## TECHNICAL SPECIFICATIONS

Recommended Use	Interior, Exterior, Indirect Contact with Food
Color Before Application	Tan
Dried Film	Light Brown
Open Time	6 to 10 minutes
Close assembly time under pressure	Normal (11-20 min.)
Viscosity	4200 cps
Brand	Titebond®
VOC Concentration (EPA Method 24)	5.6 grams per liter
Standards and Certifications	ASTM D-4236, ANSI/HPVA Type I Water-Resistance
Solid Content (Approx.)	52%
Base	Advanced Proprietary Polymer
pH	2.5
Freeze/Thaw Stability	Keep From Freezing, Stable

## APPLICATION

- Ideal for wood projects - Indoor and outdoor applications

## IMPORTANT INFORMATION

FDA approved for indirect food contact Conforms to ASTM D-4236 Complies with ANSI/HPVA Type I water-resistance standards

## PRODUCT PHOTOS



