

Straight Track for Rolling Ladders

Finish





Overall Length

36 in	72 in	96 in
-------	-------	-------

Packaging format

Per unit	Length of 6 linear foot	Length of 8 linear foot
----------	----------------------------	-------------------------

DESCRIPTION

Works with a variety of support brackets

The Straight Track for Rolling Ladders works with four types of support brackets.

- Available in four finishes: black, chrome, painted satin nickel, and satin brass
- Brackets sold separately
- Tracks can be joined with the Splice Kit
- Tracks have a slot design in the back so that support brackets can be positioned where there is solid support
- Requires a support bracket every 32 in (805 mm) or less
- Track has 1 in (25.4 mm) diameter

IMPORTANT: Refer to the maple or oak wood rolling ladder webkits for full list of components.

AVAILABLE PRODUCTS

Product #	Finish	Overall Length	Packaging format
622196900	Black (90)	96 in	Length of 8 linear foot
88400604140	Chrome (140)	72 in	Length of 6 linear foot
88400802185	Painted Satin Finish Nickel	96 in	Length of 8 linear foot
884003B160	Satin Brass	36 in	Per unit

TECHNICAL SPECIFICATIONS

Dimensions	1 in
Туре	Track
Application	Library
Manufacturing Material	Aluminum



IMPORTANT INFORMATION

We strongly recommend that you order the products TUBECART and CAP (two CAPs per TUBECART) to package this product. Please note that if you do not, returns or claims for packaging defects will not be accepted. Feel free to contact us at info@richelieu.com with questions.

DISCLAIMER

Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation.

PRODUCT PHOTOS

