



Tambour Door - Stainless Steel Finish 20 mm Slats

Minimum Interior Width

550 mm (21-21/32")

750 mm (29-17/32")

Maximum Interior Width

754 mm (29-11/16")

954 mm (37-9/16")

ADVANTAGES AND BENEFITS

- Does not require cutting. - Quick installation. - Complete components in the box. - Practical: full access to the contents of the cabinet. - Space-saving: the door opens inside the cabinet and does not obstruct the work area. - Functional: soft-opening vertical door. - Versatile: use for new applications and renovation.

AVAILABLE PRODUCTS

Product #	Minimum Interior Width	Maximum Interior Width
KITAMB30SS	550 mm (21-21/32")	754 mm (29-11/16")
KITAMB36SS	750 mm (29-17/32")	954 mm (37-9/16")

TECHNICAL SPECIFICATIONS

Material	Metal Extrusion on Polymer Base
Finish	Stainless Steel
Minimum Exterior Height	600 mm (23-5/8")
Maximum Exterior Height	1,000 mm (39-3/8")
Slat Width	25/32 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

- Kitchen and bathroom cabinets - Audio-video furniture - Residential cabinets and closets - Shop displays - Office furniture

INCLUDED PRODUCT(S)

Slats Non-Locking Metallic Handle Profile Handle Gliders Rail (Track) End Caps Cover Profile Cover Profile Base Heavy-Duty Roller System (C3 Counterbalance) #6 x 1/2" Flat Head Screws #6 x 1/2" Pan Head Screws 8 - 18 x 1" Tapping Screws 5/16 x 1" Wooden Dowels Dowels 1 Grip Handle Stopper

IMPORTANT INFORMATION

Using a 3/4" (19 mm) board thickness will leave a 3 mm reveal result. We recommend that you edge the face of the cabinet before you apply the face track. Using a 5/8" (16 mm) board thickness will leave a flush result. An internal depth of ≥ 290 mm is required for installation.

PRODUCT PHOTOS

