



## Plain Wood Dowel

### Diameter

3/16 in\*

1/4 in\*

1/4 in

5/16 in\*

3/8 in

### Length

31/32 in\*

1 3/16 in\*

1 1/4 in

1 3/8 in\*

1 1/2 in

1 9/16 in\*

1 31/32 in\*

### Packaging format

Bag of 1000  
units

Box of 10000

Box of 12000

Box of 13000

Box of 14200

Box of 29600

Box of 35400

Box of 64000

## DESCRIPTION

For manual or automatic application

## AVAILABLE PRODUCTS

Product #	Diameter	Length	Packaging format
<b>MP525T</b>	3/16 in*	31/32 in*	Bag of 1000 units
<b>525T</b>	3/16 in*	31/32 in*	Box of 64000
<b>10630T</b>	1/4 in*	1 3/16 in*	Box of 35400
<b>MP14114T</b>	1/4 in	1 1/4 in	Bag of 1000 units
<b>14114T</b>	1/4 in	1 1/4 in	Box of 29600
<b>8830TT</b>	5/16 in*	1 3/16 in*	Box of 10000
<b>835TT</b>	5/16 in*	1 3/8 in*	Box of 10000
<b>840T</b>	5/16 in*	1 9/16 in*	Box of 14200
<b>850T</b>	5/16 in*	1 31/32 in*	Box of 12000
<b>MP38112T</b>	3/8 in	1 1/2 in	Bag of 1000 units
<b>38112T</b>	3/8 in	1 1/2 in	Box of 13000

## TECHNICAL SPECIFICATIONS

<b>Type</b>	Plain Multi-Grooved Dowel
<b>Material</b>	Wood

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

---

## IMPORTANT INFORMATION

Plain wood dowel tolerances are  $\pm 0.007"$  (0.1778mm) for diameter and  $\pm 0.03125"$  (0.79375mm) for length. Note that wood is a natural product that can be affected by its environment despite being dried to a stable 6-8% moisture content.

## PRODUCT PHOTOS

