



Standoff without Ring

Height

3/4 in 1 1/2 in

DESCRIPTION

Caps included

Standoff used to support glass wall panels. When mounted on wall with a M4 x 40 mm (1-37/6") screw, the maximum load capacity for four standoffs is 30 kg (66.13 lb). The maximum size for glass panels is 1,000 mm x 500 mm (39-3/8" x 19-11/16"), and the recommended thickness is 8 mm (5/16") when using four standoffs and M4 x 40 mm (1-37/64") screws.

ADVANTAGES AND BENEFITS

Sold as a set of four standoffs, which will save you time during the execution of work. Suitable for various glass thicknesses.

AVAILABLE PRODUCTS

Product #	Height
BP31319175	3/4 in
BP31338175	1 1/2 in

TECHNICAL SPECIFICATIONS

Finish	Brushed Nickel
Glass Thickness	3/16 to 5/16 in*
Milling Diameter	9/32 in*
Material	Steel
Threaded	1/4"-20
Diameter	3/4 in
Load Capacity	33.1 to 83.8 lb*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, <u>click here</u>.

APPLICATION

Ideal for commercial applications, such as in offices or conference rooms.

INCLUDED PRODUCT(S)

Mounting screws not included



IMPORTANT INFORMATION

For safety purposes, use tempered glass. The use of power tools during installation may damage the hinges and decorative hardware. The glass must be shaped according to the section plane provided in the box. Always set the product in a suitable material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product. Maintenance: clean with a soft cloth and non-abrasive soap or ammonia. This illustration is provided for visual reference only. Actual product may differ from the illustration. Order hardware before starting the job. The manufacturer reserves the right to change product and information without notice. Always use the instructions inside the package. Drawings and technical documents contain examples of hardware from different manufacturers. The customer may in no case make a claim following the use of these documents. The Company disclaims any responsibility for the structural details related to a construction or project. Installation must be done by qualified personnel. Always make sure that the product is properly installed using suitable fixings to the support material. Never exceed the load or maximum size recommended by the manufacturer. Never use a spray lubricant on this product.

DISCLAIMER

The preceding information as well as any technical recommendation given in writing, verbally or based on tests is provided to the best of our knowledge. However, recommendations are non-binding and do not diminish your responsibility for determining the correctness of these recommendations and the suitability of the product for your particular purpose. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore exclusively your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.



PRODUCT PHOTOS







