






## Flush Bolt for Metal Doors with 12" Extension

### Color/Finish



## DESCRIPTION

### Additional safety for doors

When the active door is opened, the lever can be moved to the "up" position, retracting the bolt and allowing the inactive leaf to be opened. When the inactive leaf is closed, the lever can be moved to the "down" position, pushing the bolt into the strike and securely locking the inactive leaf. Designed with safety in mind and easy to install.

## ADVANTAGES AND BENEFITS

Unlock easily by flipping the lever.

## AVAILABLE PRODUCTS

Product #	Color/Finish
656FBV	Black
656BV	Brass
656BCV	Brushed Chrome
656NBV	Brushed Nickel
656CV	Chrome
656ORBV	Oil-Rubbed Bronze

## TECHNICAL SPECIFICATIONS

Collection	Door Flush Bolts
Width	1 in
Length	6 3/4 in
Projection	1 3/8 in
Material	Metal
Screw/Nail	Included

## INCLUDED PRODUCT(S)

Bolt tip 1/2" in diameter. Bolt throw 3/4" with a backset of 3/4". Standard rod length is 12" from the center of the bolt body to the bolt tip. - Body size: 1" wide x 6-3/4" long x 1-3/8" deep - Guide size: 1" wide x 2" long x 5/64" thick - Strike size: 15/16" wide x 2-1/4" long x 5/64" thick Screws included

## APPLICATION

Simplified installation for metal frames; round bolt head requires only a punched hole. Strike use is optional. A special guide design and flat-sided bolt tip prevent bolt rotation.

## IMPORTANT INFORMATION

Requires a mortised groove in the door 5-1/2" long x 7/8" deep.

## PRODUCT PHOTOS

