



110° CLIP top BLUMOTION Hinge

Door Position

☐ Full Overlay

☐ Half Overlay

☐ Inset

☐ Overlay

Fixing Type

☐ Dowel

☐ Expanding Dowel

☐ Inserta

☐ Screw-On

Screw/Nail

☐ Included

☐ Not Included

Packaging Specifications

☐ Industrial Packaging

☐ Retail

Packaging format

☐ Per unit

☐ Bag

☐ Bag of 2 units

DESCRIPTION

Integrated BLUMOTION

Precise movement, like clockwork. Integrated BLUMOTION is a technical masterpiece that fits into the smallest of spaces and provides your furniture doors with silent, effortless closing.

CLIP top BLUMOTION is designed to open and close at least 200,000 times, with a compelling quality of motion, to last the lifetime of the furniture.

ADVANTAGES AND BENEFITS

- Innovative technology concentrated into the smallest space, with BLUMOTION integrated into the hinge cup.
- Silent, effortless closing action provides every door with inspiringly perfect motion.
- Effortless closing even for small doors; Blumotion can optionally be deactivated.
- Elegant design for a high-quality look, with compelling technology in a stylish body.
- All-metal hinge, nickel-plated.
- Convenient spiral-tech depth adjustment.
- Compatible with existing mounting plates.
- Features spring closing mechanism.
- Tool-free door-to-cabinet assembly and removal.
- 3-dimensional adjustment with the appropriate mounting plate.
- Features Inserta tool-free cup installation.

AVAILABLE PRODUCTS

Product #	Door Position	Fixing Type	Screw/Nail	Packaging Specifications	Packaging format
71B358180	Full Overlay	Dowel	Not Included	Industrial Packaging	Per unit
71B358E180	Full Overlay	Expanding Dowel	Not Included	Industrial Packaging	Per unit
71B359180	Full Overlay	Inserta	Not Included	Industrial Packaging	Per unit
BP71B35523180	Full Overlay	Screw-On	Included	Industrial Packaging	Bag of 2 units
71B355180	Full Overlay	Screw-On	Not Included	Industrial Packaging	Per unit
71B368180	Half Overlay	Dowel	Not Included	Industrial Packaging	Per unit
71B369180	Half Overlay	Inserta	Not Included	Industrial Packaging	Per unit
BP71B36523180S	Half Overlay	Screw-On	Included	Retail	Bag of 2 units
71B365180	Half Overlay	Screw-On	Not Included	Industrial Packaging	Per unit
71B378180	Inset	Dowel	Not Included	Industrial Packaging	Per unit
71B379180	Inset	Inserta	Not Included	Industrial Packaging	Per unit
BP71B37523180	Inset	Screw-On	Included	Industrial Packaging	Bag of 2 units
BP71B37523180S	Inset	Screw-On	Included	Retail	Bag of 2 units
71B375180	Inset	Screw-On	Not Included	Industrial Packaging	Per unit
BP71B35523180U	Overlay	Screw-On	Included		Bag

TECHNICAL SPECIFICATIONS

Use Type	Standard Door
Cabinet Type	Frameless
Finish	Nickel
Closing Mechanism	Self-Closing
Cabinet Thickness	Min. 19/32 in*
Door Thickness	Min. 19/32 in*
Hinge Type	CLIP top BLUMOTION
Milling Depth	1/2 in*
Milling Diameter	1 3/8 in*
Hinge Opening Angle	+110°
Closing Mechanism	Soft-Closing
Material	Steel

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

- Do not use a hammer to insert the hinge into the drilled hole. - CLIP top BLUMOTION hinges should be operated within the temperature range of 18 °C and 28 °C to ensure optimal functioning. - Because BLUMOTION function now comes integrated with the hinge, additional assembly processes are no longer necessary after the installation is completed. - For drilling on melamine 5/8, please use the item M01ZB3502, a drill bit shape without tip. *** For a greater selection of mounting plates, please refer to the BLUM mounting plates section ***

APPLICATION

- For the installation of a door on a piece of furniture and/or a cabinet. - Blum hinges are not made of stainless steel, therefore it is not recommended to use them for outdoor applications.

PRODUCT PHOTOS





