



148BC Pocket Door Frame and Hardware Kit

Load Capacity

150 lb	250 lb
--------	--------

Overall Length

72 in	96 in
-------	-------

Door Height

80 in	84 in	96 in
-------	-------	-------

Door Width

24 to 36 in	24 to 48 in
-------------	-------------

Roller Type

Axle (Bushing)	Ball Bearing
-------------------	--------------

Packaging format

Box	Per unit
-----	----------

DESCRIPTION

Quick and easy installation

Complete steel system for wood pocket doors. Kit for 2 x 4 construction. Set for concealed pocket door installation. Width is adjustable to fit the wall interior with various wall thickness and various wall materials and structures.

ADVANTAGES AND BENEFITS

Can be cut to door dimensions.

AVAILABLE PRODUCTS

Product #	Load Capacity	Overall Length	Door Height	Door Width	Roller Type	Packaging format
148150BC	150 lb	72 in	80 in	24 to 36 in	Axle (Bushing)	Per unit
1485150BC	150 lb	72 in	80 in	24 to 36 in	Ball Bearing	Per unit
1487150BC	150 lb	72 in	84 in	24 to 36 in	Ball Bearing	Per unit
1488150BC	150 lb	72 in	96 in	24 to 36 in	Ball Bearing	Per unit
1488250BC	250 lb	96 in	96 in	24 to 48 in	Ball Bearing	Box

TECHNICAL SPECIFICATIONS

Door Material	Wood
Door Thickness	1 3/8 to 1 3/4 in
Finish	Mill Finish (M), Mill Finish
Packaging Format	White Cardboard with Photo Label
Product type	Hardware for Bypassing Doors
Manufacturing Material	Aluminum
Number of Doors	1
Door Position	Concealed Inside Wall
Roller Position	Upper
Door Movement	Pocket Door, Straight Sliding
Track Mounting	Ceiling Mount
Groove Needed for Guiding System	No
Soft-Closing	No
Brand	Onward
Application	Closet and Walk-In Closet, Storage, Pocket Door

INCLUDED PRODUCT(S)

Two roller carriers with 4 ball bearings and an extruded aluminum track. Steel studs have wood inserts to attach plywood panels.

IMPORTANT INFORMATION

Please note: Picture provided for visual reference only: actual product may vary. All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify or otherwise supplement any previously issued product and/or technical information without prior notice. All technical drawings and documents on this page present installation examples that use fittings from different manufactures. The client cannot under any circumstances make a claim following use of these documents. Richelieu expressly disclaims any liabilities for structure details linked to a structure or a project. Installation of the product shall always be executed by qualified individuals only. Ensure that the product is securely installed using proper fixation methods, as appropriate for each applicable substratum. Never exceed maximum load or dimensions recommended by the manufacturer. Never spray aerosol lubricant on these products. Always remove debris/dust/residues (sawdust and/or aluminum) from the rails using a dry cloth before installing carriages bearing.

APPLICATION

For bi-parting door application, use 24625005IP kit

DISCLAIMER

Note: Picture for visual reference only: actual product may vary from that shown in photo. Be sure to order hardware before beginning fabrication or installation work. Always use the instructions inside the packaging provided by the manufacturer, as the manufacturer reserves the right to make technical changes or modify information without prior notice. All technical drawings and documents contain examples for the assembly of different suppliers' hardware. The customer cannot make any claims based on the use of these documents. No responsibility is assumed for design details relating to a construction or project. At all times, execution and installation must be undertaken by qualified persons. Never exceed the maximum weight or the maximum dimensions recommended by the manufacturer. Always be sure to install the product correctly using the appropriate fixation for your material. Use a dry cloth to remove fragments, dust, and residue (wood and/or aluminum sawdust) from rails before the installation of the hangers. Never use any spray lubricant on these products. Disclaimer: The preceding information as well as any technical recommendations given in writing, verbally or based on tests are provided to the best of our knowledge. However, they are non-binding recommendations only and do not affect your responsibility to determine the correctness of given recommendations and suitability of the product for your particular purposes. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore fall exclusively in your area of responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

