





Quickfit-Expando Housing Outrigger - Top assembly only

Panel Thickness



Drilling Depth

1/2 in*	9/16 in*

Quantities per case available

500 units

Finish

Almond	Antique White	Black	Bronze	Brown
Dark Brown	Light Gray	Nickel	Silver	Warm Cherry
White				

DESCRIPTION

Top assembly only

For increased strength. 10 mm diameter reinforcement dowel located 32 mm from the bracket.

ADVANTAGES AND BENEFITS

- Extra dowel drilling ensures the housing will go in straight. - Attains maximum strength when the cam is locked.



AVAILABLE PRODUCTS

Product #	Panel Thickness	Drilling Depth	Quantities per case available	Finish
643940	5/8 in*	1/2 in*	1250 units	Almond
643930	5/8 in*	1/2 in*	1250 units	White
8644140	3/4 in*	9/16 in*	1250 units	Almond
86441301	3/4 in*	9/16 in*	1250 units	Antique White
8644190	3/4 in*	9/16 in*	1250 units	Black
86441135	3/4 in*	9/16 in*	1250 units	Bronze
8644160	3/4 in*	9/16 in*	1250 units	Brown
86441609	3/4 in*	9/16 in*	1250 units	Dark Brown
86441105	3/4 in*	9/16 in*	1250 units	Light Gray
8644106	3/4 in*	9/16 in*	1250 units	Silver
8644108	3/4 in*	9/16 in*	1250 units	Warm Cherry
8644130	3/4 in*	9/16 in*	1250 units	White
6457	3/4 in*	9/16 in*	500 units	Nickel

TECHNICAL SPECIFICATIONS

Titus System Number	System 6
Drilling Diameter	25/32 in*
Insertion Type	Drop-On
Drive Type	Phillips
Application	Quickfit-Expando Housing
Flange	With Flange
Material	Plastic

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, <u>click here</u>.



PRODUCT PHOTOS

