



Multi-Purpose Toggling Anchor

Packaging format

Blister of 10 units

Box of 30

DESCRIPTION

These plastic anchors for hollow doors and panels are shock- and vibration-resistant. They should be used on 1/8 in to 1/4 in surfaces and indoors only.

ADVANTAGES AND BENEFITS

The most versatile anchor: strong in drywall, and strong in concrete.

AVAILABLE PRODUCTS

Product #	Packaging format
TGPT12VDMX	Blister of 10 units
TGPT12VVA	Box of 30

TECHNICAL SPECIFICATIONS

Compatible Materials	Drywall, Tile, Plaster, Concrete, Block, Brick
Mounting Location	Wall, Ceiling
Screw Size	#8
Included Products	TGPTKEY Included
Material	Plastic
Load Capacity - Wall Mounted/Drywall	75 lb*
Load Capacity - Ceiling Mounted/Drywall	28.7 lb*
Load Capacity - Wall Mounted/Concrete	128 lb*
Load Capacity - Ceiling Mounted/Concrete	39.7 lb*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

INCLUDED PRODUCT(S)

For drywall, tile, plaster, concrete, block, and brick.

IMPORTANT INFORMATION

- Rust-resistant screws

PRODUCT PHOTOS

