



Industrial Black General Duty Polypropylene Caster

Load Capacity Per Caster

Max. 126 lb*

Max. 176 lb*

Max. 209 lb*

Max. 247 lb*

Max. 441 lb*

Wheel Diameter

1 31/32 in*

2 15/32 in*

2 15/16 in*

3 in*

4 1/32 in*

5 in*

Total Height

2 7/16 in*

3 7/32 in*

3 13/16 in*

5 in*

6 1/2 in*

Tread Width

25/32 in*

1 1/8 in*

1 1/4 in*

1 31/32 in*

Fastening Type



Fixed


Swivel with
Brake

Swivel
Without Brake

Mounting Plate Dimensions

1 1/2 in x 2
11/16 in (38
mm x 68 mm)

1 29/32 in x 2
9/16 in (48
mm x 65 mm)

1 7/8 in x 2
9/16 in (48
mm x 65 mm)

2 17/32 in x 3
21/32 in (64
mm x 93 mm)

2 3/8 in x 3
5/8 in (60 mm
x 92 mm)

2 7/16 in x 4
7/8 in (62 mm
x 124 mm)

2 7/32 in x 4
15/32 in (56
mm x 113
mm)

3 1/8 in x 4
1/8 in (79.5
mm x 105
mm)

3 7/8 in x 2
3/4 in (98 mm
x 70 mm)

4 in x 4 1/2 in
(102 mm x
114 mm)

DESCRIPTION

Non-marking rubber tread

Industrial black general-duty polypropylene caster. These heavy-duty casters are durable and designed for use in the most demanding environments. Available in two heights.

ADVANTAGES AND BENEFITS

- Non-marking rubber tread - Light-weight, low-cost, impact-resistant, resists water and chemical absorption - Corrosion-resistant zinc finish

AVAILABLE PRODUCTS

Product #	Load Capacity Per Caster	Wheel Diameter	Total Height	Tread Width	Fastening Type	Mounting Plate Dimensions
F25827	Max. 126 lb*	1 31/32 in*	2 7/16 in*	25/32 in*	Fixed	1 1/2 in x 2 11/16 in (38 mm x 68 mm)
F25232	Max. 126 lb*	1 31/32 in*	2 7/16 in*	25/32 in*	Swivel with Brake	1 7/8 in x 2 9/16 in (48 mm x 65 mm)
F25190	Max. 126 lb*	1 31/32 in*	2 7/16 in*	25/32 in*	Swivel Without Brake	1 29/32 in x 2 9/16 in (48 mm x 65 mm)
F25828	Max. 176 lb*	2 15/32 in*	3 7/32 in*	1 1/8 in*	Fixed	2 7/32 in x 4 15/32 in (56 mm x 113 mm)
F25233	Max. 176 lb*	2 15/32 in*	3 7/32 in*	1 1/8 in*	Swivel with Brake	3 7/8 in x 2 3/4 in (98 mm x 70 mm)
F25188	Max. 176 lb*	2 15/32 in*	3 7/32 in*	1 1/8 in*	Swivel Without Brake	3 7/8 in x 2 3/4 in (98 mm x 70 mm)
F25189	Max. 209 lb*	2 15/16 in*	3 13/16 in*	1 1/4 in*	Swivel Without Brake	3 1/8 in x 4 1/8 in (79.5 mm x 105 mm)
F25829	Max. 209 lb*	3 in*	3 13/16 in*	1 1/4 in*	Fixed	2 7/16 in x 4 7/8 in (62 mm x 124 mm)
F25234	Max. 209 lb*	3 in*	3 13/16 in*	1 1/4 in*	Swivel with Brake	3 1/8 in x 4 1/8 in (79.5 mm x 105 mm)
F25830	Max. 247 lb*	4 1/32 in*	5 in*	1 1/4 in*	Fixed	2 3/8 in x 3 5/8 in (60 mm x 92 mm)
F25223	Max. 247 lb*	4 1/32 in*	5 in*	1 1/4 in*	Swivel with Brake	2 17/32 in x 3 21/32 in (64 mm x 93 mm)
F25187	Max. 247 lb*	4 1/32 in*	5 in*	1 1/4 in*	Swivel Without Brake	2 17/32 in x 3 21/32 in (64 mm x 93 mm)
F26905	Max. 441 lb*	5 in*	6 1/2 in*	1 31/32 in*	Swivel Without Brake	4 in x 4 1/2 in (102 mm x 114 mm)

TECHNICAL SPECIFICATIONS

Mounting Type	Plate
Material	Polypropylene
Recommended Surfaces	Concrete, Carpet, Steel, Wood/Planking
Finish	Black
Conditions	Water, Solvents, Detergent, Acids, Petroleum Products

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

DISCLAIMER

Technical data subject to change without prior notice.

PRODUCT PHOTOS

