

Industrial Polyamide Rubber Caster

Total Height

6 11/32 in*

6 3/8 in*

Fastening Type



Fixed


Swivel with
Double-Lock
Brake

Swivel
Without Brake

Mounting Plate Dimensions

3 11/32 in x 4
1/8 in (85 mm
x 105 mm)

3 3/8 in x 4
3/32 in (85.5
mm x 104
mm)

DESCRIPTION

Non-marking rubber tread

Industrial polyamide rubber caster. These heavy-duty casters are designed for use in the most demanding environments. Available with fixed plate, swivel, or double locking.

ADVANTAGES AND BENEFITS

- Non-marking rubber tread - Low starting effort, rolls easily - Double-lock braking system locks both the wheel and the swivel (F24804) - Hight impact-resistant polyamide inner and outer rings; shock-absorbing central rubber ring

AVAILABLE PRODUCTS

Product #	Total Height	Fastening Type	Mounting Plate Dimensions
F24806	6 11/32 in*	Fixed	3 3/8 in x 4 3/32 in (85.5 mm x 104 mm)
F24804	6 3/8 in*	Swivel with Double-Lock Brake	3 11/32 in x 4 1/8 in (85 mm x 105 mm)
F24805	6 3/8 in*	Swivel Without Brake	3 11/32 in x 4 1/8 in (85 mm x 105 mm)

TECHNICAL SPECIFICATIONS

Load Capacity Per Caster	Max. 441 lb*
Wheel Diameter	4 29/32 in*
Tread Width	1 3/8 in*
Mounting Type	Plate
Material	Polyamide
Recommended Surfaces	Concrete, Carpet, Wood/Planking, Asphalt
Finish	Beige, Blue
Axle Diameter	5/16 in*
Axle Length	1 23/32 in*
Mounting Hole Diameter	11/32 in*
Conditions	Water, Solvents, Detergent, Extreme Cold, Extreme Heat, Petroleum Products

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

For all additional measurements, please see the technical documents.

DISCLAIMER

Technical data subject to change without prior notice.

PRODUCT PHOTOS

