



3-Axis Adjustable Concealed Hinge

Minimum Door Thickness

1 1/8 in

1 7/16 in

Finish

Black

Dull Chrome

Dull Nickel

Maximum Capacity (2 Hinges)

66.1 lb*

220 lb*

Maximum Capacity (3 Hinges)

88.2 lb*

276 lb*

DESCRIPTION

3-axis adjustment

ADVANTAGES AND BENEFITS

- Enables vertical, horizontal, and depth adjustment after installation. - Easy to install and remove.

AVAILABLE PRODUCTS

Product #	Minimum Door Thickness	Finish	Maximum Capacity (2 Hinges)	Maximum Capacity (3 Hinges)
753120175	1 1/8 in	Dull Chrome	66.1 lb*	88.2 lb*
753120195	1 1/8 in	Dull Nickel	66.1 lb*	88.2 lb*
75319090	1 7/16 in	Black	220 lb*	276 lb*
753190175	1 7/16 in	Dull Chrome	220 lb*	276 lb*
753190195	1 7/16 in	Dull Nickel	220 lb*	276 lb*

TECHNICAL SPECIFICATIONS

Material	Zinc Alloy
Type of Hinge	Wood Door Only
Brand	Sugatsune

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

INCLUDED PRODUCT(S)

- Stainless steel flat-headed screw (screw heads are painted).

IMPORTANT INFORMATION

Note: The hardware must be ordered before the execution of the project. Picture for visual reference only: actual product may vary from that shown in photo. Always use the instruction supplied by the manufacturer inside of the packaging because the manufacturer reserves the right to make technical changes or modify information without prior notice. At all times, execution and installation must be undertaken by qualified persons. Always be sure to install the product correctly using the appropriate fixation for your material. Never exceed the maximum weight or the maximum width recommended by the manufacturer. Never use any spray lubricant on these products. Never used any spray lubricant on these products. Care: Use a soft cloth and a mild soap without ammonia or abrasives.

Disclaimer: The preceding information, as well as any technical recommendations given in writing, verbally or based on tests, is provided to the best of our knowledge. However, recommendations are non-binding and do not affect your responsibility to determine the correctness of the given recommendations and the suitability of the product for your particular purposes. The application, use, or processing of our products, as well as the production of products based on our technical recommendations, are out of our control and therefore fall exclusively under your responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

