

G Suspension Profile, HAWA

Compatible with

Hawa Junior /
Hawa
Telescopic

Hawa
Variotec /
Hawa
Variofold and
Centerfold

Overall Height

3 5/8 in*

4 1/8 in*

Width

1 1/32 in*

1 13/32 in*

Door Thickness

5/16 to 13/32
in*

5/16 to 5/8 in*

15/32 to 1/2
in*

DESCRIPTION

For Junior, Telescopic, Variotec

The G Suspension Profile is for HAWA sliding glass door systems in the Junior, Telescopic and Variotec series. A choice of three aluminum profiles are available for different glass thicknesses and series. In brushed anodized aluminum.

AVAILABLE PRODUCTS

Product #	Compatible with	Overall Height	Width	Door Thickness
65921782G	Hawa Junior / Hawa Telescopic	3 5/8 in*	1 1/32 in*	5/16 to 13/32 in*
65921784G	Hawa Junior / Hawa Telescopic	3 5/8 in*	1 1/32 in*	5/16 to 5/8 in*
65923443G	Hawa Variotec / Hawa Variofold and Centerfold	4 1/8 in*	1 13/32 in*	15/32 to 1/2 in*

TECHNICAL SPECIFICATIONS

Product type	Decorative Hardware
Door Material	Glass
Finish	Brushed Anodized
Door Installation	Top Hung
Load Capacity	353 lb*
Manufacturing Material	Aluminum
Brand	Hawa
Overall Length	47 1/4 in*
Door Movement	Straight Sliding, Movable Wall
Detailed Door Movement	Telescoping
Application	Standard Access Door

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

IMPORTANT INFORMATION

- Please read the entirety of the installation manual before proceeding with installation. - Wear safety gear such as gloves, safety glasses, safety shoes and ear protection - Every fastener used to attach the track to the wall must be fastened securely into a structural surface. - Always remove debris/dust/residue (sawdust and/or aluminum) from all tracks and guide channels using a dry cloth during installation and before operating the system. - Never spray lubricant on this product. - Do not exceed stated limitations and parameters. This will cause early wear and performance failure.

DISCLAIMER

Pictures provided for visual reference only: actual product may vary. - All required hardware should be ordered and obtained prior to initiating fabrication or installation work. Please verify that the parts and quantities listed in your order are correct before proceeding to checkout. - Always use instructions provided by the manufacturer, as included with the product. Manufacturer reserves the right to amend, modify, or otherwise supplement any previously issued product and/or technical information, as deemed required from time to time, without prior notice. - The documentation, drawings, and instructions on this page apply to the system described on this page only. Richelieu expressly declines all responsibility for any design or construction that combines this system with systems from this same manufacturer or systems from other manufacturers. - Installation of the product shall be executed by qualified individuals only, always ensuring that each product is securely installed using proper fixation methods, as appropriate for each applicable substratum. We trust that anyone installing these products has the required skills, knowledge, and experience. Richelieu expressly disclaims any liabilities for results obtained through improper use or installation.

PRODUCT PHOTOS

