



FineLine LED Strip Lights

Light Color

Cool White

Warm White

Kelvin Color Temperature (K)

3000 K

5000 K

Length

8 in

12 in

22 in

Watts

1.6 W

2.4 W

4.4 W

DESCRIPTION

Sturdy aluminum body

Long and narrow, FineLine is the unobtrusive way to provide smooth, linear lighting almost anywhere.

The low profile design features a frosted diffuser for even illumination. With optional manual or remote control dimmers, creating the perfect atmosphere is effortless.

The FineLine is available in 3 lengths:

- 203 mm (8")
- 305 mm (12")
- 559 mm (22")

The FineLine can link light to light without a link cord.

It's as easy as a snap.

There are no gaps, no dark spots, only a continuous line of light.

The FineLine features a sturdy aluminum body.

ADVANTAGES AND BENEFITS

- The low-profile FineLine features a frosted diffuser for perfect, even illumination.
- An optional Inline Touch Dimmer attaches directly or remotely via link cord to the light and features four dimming levels (lo-med-hi-off).
- Manual or remote control dimmers are also offered.
- Average rated life: 50,000 hours.
- Extremely thin, low-profile design - 90° beam spread
- Frosted diffuser
- Available in three lengths
- Dimmable

AVAILABLE PRODUCTS

Product #	Light Color	Kelvin Color Temperature (K)	Length	Watts
LLEDSTK8CNI	Cool White	5000 K	8 in	1.6 W
LLEDSTK12CNI	Cool White	5000 K	12 in	2.4 W
LLEDSTK22CNI	Cool White	5000 K	22 in	4.4 W
LLEDSTK8WNI	Warm White	3000 K	8 in	1.6 W
LLEDSTK12WNI	Warm White	3000 K	12 in	2.4 W
LLEDSTK22WNI	Warm White	3000 K	22 in	4.4 W

TECHNICAL SPECIFICATIONS

Location	Inside Cabinet, Closet, Other
Application	Kitchen
Mounting	Surface
Luminaire	Rigid Linear
Lighting	Accent
Finish	Aluminum
Standards and Certifications	UL
Style	Contemporary, Functional
Height	5/16 in
Lighting Type	LED
Tension (V)	12 V

APPLICATION

- Shelving - Displays or store fixtures - Interior and under cabinets

INCLUDED PRODUCT(S)

Included with each light: - the FineLine - 2 m (79") starter cord - AMP connector - 2 mounting clips (straight & adjustable mounting U-Clips) with screws

IMPORTANT INFORMATION

- Maximum continuous run: 12 feet to prevent voltage drop. - Maximum 24 feet per 60 W power supply.

DISCLAIMER

- All product dimensions and specifications are subject to change without prior notice. - LED is not replaceable. - Not intended to be used in damp locations or outdoor areas.

PRODUCT PHOTOS



► Optional in-line touch dimmer available
(4-step: low-medium-high-off)



► Linkable (back-to-back or link cord)
up to 12' (3.66 m) continuous run



► Straight & adjustable mounting U-Clips included



► 79" (2 m) starter cord included

