




Surface-Mount Floor Register - Wood

Species




Duct Opening - Width



Duct Opening - Length



Width - Overall Dimensions



Length - Overall Dimensions



DESCRIPTION

Surface-mounted floor register.

ADVANTAGES AND BENEFITS

- Can be used on all floor coverings.
- Can replace any existing metal or plastic register.
- Polished with 180 grit and ready for finishing.
- Select and better grade wood.
- Adjustable ventilation flow.
- Elegant design.
- Very sturdy.
- Will not rust.

AVAILABLE PRODUCTS

Product #	Species	Duct Opening - Width	Duct Opening - Length	Width - Overall Dimensions	Length - Overall Dimensions
RS2141203	Birch	2 1/4 in	12 in	3 1/4 in	13 1/8 in
RS31003	Birch	3 in	10 in	4 in	11 1/8 in
RS41003	Birch	4 in	10 in	5 in	11 1/8 in
RS41203	Birch	4 in	12 in	5 in	13 1/8 in
RS2141215	Maple	2 1/4 in	12 in	3 1/4 in	13 1/8 in
RS31015	Maple	3 in	10 in	4 in	11 1/8 in
RS41015	Maple	4 in	10 in	5 in	11 1/8 in
RS41215	Maple	4 in	12 in	5 in	13 1/8 in
RS41025	Red Oak	4 in	10 in	5 in	11 1/8 in
RS41225	Red Oak	4 in	12 in	5 in	13 1/8 in

TECHNICAL SPECIFICATIONS

Material	Wood
Model	Surface Mount
Production Delay	In Stock
Projection - Overall Dimensions	3/4 in
Color Group	Wood Group

IMPORTANT INFORMATION

When varnishing the register, it is important to varnish the entire register so that the timber maintains a stable moisture content between 6% and 9%. This will prevent the register from bending due to ventilation.

PRODUCT PHOTOS

