



Tambour Door - Aluminum Finish 25 mm Slats

Exterior Width

18 in	30 in	36 in
-------	-------	-------

DESCRIPTION

Robust roller mechanism - C3

Tambour doors provide a unique and high quality detail in interior planning, especially in kitchens and offices.

ADVANTAGES AND BENEFITS

- Does not require cutting. - Quick installation. - Complete components in the box. - Practical: full access to the contents of the cabinet. - Space-saving: the door opens inside the cabinet and does not obstruct the work area. - Functional: soft-opening vertical door. - Versatile: use for new applications and renovation.

AVAILABLE PRODUCTS

Product #	Exterior Width
KITAMB18ALU25MM	18 in
KITAMB30ALU25MM	30 in
KITAMB36ALU25MM	36 in

TECHNICAL SPECIFICATIONS

Material	Metal Extrusion on Polymer Base
Finish	Aluminum
Exterior Height	48 in
Slat Width	31/32 in*

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, click here.

APPLICATION

- Kitchen and bathroom cabinets - Audio-video furniture - Residential cabinets and closets - Shop displays - Office furniture

INCLUDED PRODUCT(S)

Slats Non-Locking Metallic Handle Profile Handle Gliders Rail (Track) End Caps Cover Profile Cover Profile Base Heavy-Duty Roller System (C3 Counterbalance) #6 x 1/2" Flat Head Screws #6 x 1/2" Pan Head Screws 8 - 18 x 1" Tapping Screws 5/16 x 1" Wooden Dowels 1 Grip Handle Stopper



IMPORTANT INFORMATION

The dimensions of the set are based on the external dimensions of cabinets and are suitable for a three-sided cabinet. A notch in the rail is required for a four-sided cabinet. Using a panel with a thickness of 5/8" (16 mm) gives a precise finish between the panel and rail, while the use of a panel with a thickness of 3/4" (19 mm) gives a finish that reveals 3 mm of panel. An internal depth of >=290 mm is required for installation.

PRODUCT PHOTOS



