

## Torque Hinge

### Width - Overall Dimensions

1 13/32 in\*

1 7/8 in\*

### Height

5/16 in\*

11/32 in\*

### Torque

3.1 lb/in

6.2 lb/in

### Depth

1 1/4 in\*

1 9/16 in\*

## DESCRIPTION

Stainless steel torque hinge.

## ADVANTAGES AND BENEFITS

- Hinge with friction torque holds lid or door in desired position. - Stainless steel material ideal for harsh environment. - Free stop between 1 to 180 degrees. - Successfully passed 20,000 open/close private cycle tests.

## AVAILABLE PRODUCTS

Product #	Width - Overall Dimensions	Height	Torque	Depth
750336171	1 13/32 in*	5/16 in*	3.1 lb/in	1 1/4 in*
750748171	1 7/8 in*	11/32 in*	6.2 lb/in	1 9/16 in*

## TECHNICAL SPECIFICATIONS

Material	Stainless Steel, Stainless Steel 304
Color/Finish	Polished
Brand	Sugatsune
Standards and Certifications	ROHS/WEEE

### Disclaimer

Measures shown with an asterisk (\*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

## IMPORTANT INFORMATION

- Initial torque may vary from 20% to 40% - At least 2 hinges are necessary for 1 door.

## PRODUCT PHOTOS

