



Heavy-Duty Galvanized Steel Box Rail

Overall Length

6 ft	8 ft	10 ft	12 ft
------	------	-------	-------

Packaging format

Length of 6 linear foot	Length of 8 linear foot	Length of 10 linear foot	Length of 12 linear foot
-------------------------	-------------------------	--------------------------	--------------------------

DESCRIPTION

Commercial trolley track for sliding doors on heavy-duty industrial, garage and barn doors. Easy to install. Secure and sleek design.

ADVANTAGES AND BENEFITS

Can be used with various types of single and multiple brackets.

AVAILABLE PRODUCTS

Product #	Overall Length	Packaging format
24654115GABC	6 ft	Length of 6 linear foot
24654116GABC	8 ft	Length of 8 linear foot
24654117GABC	10 ft	Length of 10 linear foot
24654118GABC	12 ft	Length of 12 linear foot

TECHNICAL SPECIFICATIONS

Product type	Track, Box Track
Door Material	Aluminum/Metal Frame, Wood
Door Position	In Front of Wall, Inside Frame
Track Mounting	Ceiling Mount, Wall Mount
Roller Position	Upper
Door Thickness	1 1/2 to 3 1/2 in
Track type	Running
Width	1 31/32 in
Load Capacity	Max. 450 lb
Finish	Galvanized
Manufacturing Material	Steel
Screw/Nail Included	No
Overall Height	2 7/16 in
Application	Barn Door
Gauge	16

APPLICATION

Industrial, garage, and barn doors.

IMPORTANT INFORMATION

Fasteners and brackets sold separately. For doors weighing up to 450 lb per panel. Note: Picture for visual reference only: actual product may vary from that shown in photo. Be sure to order hardware before beginning fabrication or installation work. Always use the instructions inside the packaging provided by the manufacturer, as the manufacturer reserves the right to make technical changes or modify information without prior notice. All technical drawings and documents contain examples of the assembly of different suppliers' hardware. The customer cannot base any claims on the use of these documents. No responsibility is assumed for design details relating to a particular construction project. At all times, execution and installation must be undertaken by qualified persons. Never exceed the maximum weight or the maximum dimensions recommended by the manufacturer. Always be sure to install the product correctly using the right fasteners for your materials. Never use any spray lubricant on these products.

DISCLAIMER

The preceding information, as well as any technical recommendations given in writing, verbally or based on tests, is provided to the best of our knowledge. However, they are non-binding recommendations only and do not affect your responsibility to determine the correctness of given recommendations and suitability of the product for your particular purposes. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore fall exclusively in your area of responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

