



Heavy Duty Galvanized Steel Box Rail with Flashing

Overall Length

8 ft

10 ft

12 ft

Packaging format

Length of 8 linear foot

Length of 10 linear foot

Length of 12 linear foot

DESCRIPTION

Commercial trolley track with flashing for sliding doors on heavy-duty industrial garage and barn doors. Generally used for exterior doors and purposes. Simple installation.

ADVANTAGES AND BENEFITS

No brackets required as the flashing provides continuous bracket support and prevents the accumulation of snow and ice.

AVAILABLE PRODUCTS

Product #	Overall Length	Packaging format
24651088GABC	8 ft	Length of 8 linear foot
24651089GABC	10 ft	Length of 10 linear foot
24651090GABC	12 ft	Length of 12 linear foot

TECHNICAL SPECIFICATIONS

Product type	Track, Box Track
Door Material	Aluminum/Metal Frame, Wood
Door Position	In Front of Wall
Track Mounting	Wall Mount
Door Thickness	1 1/2 to 3 1/2 in
Track type	Running
Width	1 7/8 in
Load Capacity	Max. 450 lb
Finish	Galvanized
Overall Height	2 3/8 in

APPLICATION

Garage, sliding barn, industrial doors.

IMPORTANT INFORMATION

For doors weighing up to 450 lbs per panel. Note: Picture for visual reference only: actual product may vary from that shown in photo. Be sure to order hardware before beginning fabrication or installation work. Always use the instructions inside the packaging provided by the manufacturer, as the manufacturer reserves the right to make technical changes or modify information without prior notice. All technical drawings and documents contain examples of the assembly of different suppliers' hardware. The customer cannot base any claims on the use of these documents. No responsibility is assumed for design details relating to a particular construction project. At all times, execution and installation must be undertaken by qualified persons. Never exceed the maximum weight or the maximum dimensions recommended by the manufacturer. Always be sure to install the product correctly using the right fasteners for your materials. Never use any spray lubricant on these products.

DISCLAIMER

The preceding information, as well as any technical recommendations given in writing, verbally or based on tests, is provided to the best of our knowledge. However, they are non-binding recommendations only and do not affect your responsibility to determine the correctness of given recommendations and suitability of the product for your particular purposes. The application, use or processing of our products as well as the production of products based on our technical recommendations are beyond our control and therefore fall exclusively in your area of responsibility. Sales of our products are subject to our most recent General Sales and Delivery Conditions. Please note that Richelieu will not accept any returns or claims for unpackaged products.

PRODUCT PHOTOS

