



DAP® DYNAFLEX 230® Premium Indoor/Outdoor Sealant

Finish

DESCRIPTION

Waterproof, window, door and trim sealant

DAP® DYNAFLEX 230® delivers a "silicone tough" latex formulation for outstanding exterior performance against the elements. Developed for flexibility and crack proof performance, this sealant endures expansion and contraction without cracking or losing its seal. The paintable, durable sealant can fill gaps up to 25.4 cm (1") wide and the cured sealant is mold and mildew resistant. It has excellent adhesion to a wide range of building materials including wood, MDF, PVC, polystyrene and composite trimboard.

ADVANTAGES AND BENEFITS

- A premium latex sealant with the performance characteristics of non-industrial acetoxysilicone products - Easy to gun out - Tools smoothly - Easy clean-up with soap and water - Paintable - Low odor - Highly flexible to handle joint movement caused by variations in temperature and humidity without cracking - Provides a long-lasting, durable seal that is 100% waterproof and weatherproof

AVAILABLE PRODUCTS

Product #	Finish
D015827	Clear
D015825	White

TECHNICAL SPECIFICATIONS

Brand	DAP
Ideal Use	Aluminum Windows, Wood Windows, Vinyl (PVC) Windows, Exterior Trim & Siding
Base	Acrylic Latex Polymer
Optimal adherence to	Concrete, Glass, Plastic, Brick, Aluminum, Stone, Steel, Painted metal, Vinyl, Masonry, PVC
Tooling Time	10 minutes
Volume	10.1 oz*
Weight	10.1 oz
Properties	Paintable
Packaging Specifications	Plastic Cartridge
Standards and Certifications	ASTM C834, ASTM C920

Disclaimer

Measures shown with an asterisk (*) have been converted as per your preference. These are not the official measures. To view the measures specified by the manufacturer, [click here](#).

APPLICATION

Ideal for Caulking and Sealing: - Windows and doors - Pipes - Siding and trim - Molding - Butt joints - Tuck-pointing - Baseboards - Vents - Corner joints - Other gaps and cracks

IMPORTANT INFORMATION

Meets ASTM Specification C920, Class 25.

PRODUCT PHOTOS

